ecision.con Visit our NEW



**TOOL-A-THON** 

Volume 15.1

# **HEIGHT GAGES**

# **FOWLER-TRIMOS V3 & V4 ELECTRONIC HEIGHT GAGES**

The NEW Fowler-Trimos V3 and V4 vertical measuring instruments have been developed for the most difficult workshop environments. Manufactured in their entirety in Switzerland, they quarantee a robust, precise and reliable product in the long run.

- Measuring ranges 400mm and 700mm
- Extremely easy to use"Black mask" display with user friendly functions
- · Electronically adjustable measuring force
- Battery life: approximately 40 hours (lithium-ion batteries)
- · Vast range of accessories
- All adjustments possible without tools
- · Cast iron base for optimal stability RS232 and USB interfaces
- Air cushion (V4 Only)
- Dual probe holders (V4 Only)
   Measures heights, diameters, perpendicularity, centerlines, Min/Max/Delta
- Accessory measuring probes up to 340mm in length available and provide excellent repeatability

#### V3 and V4 includes:

- · Charging unit
- Measuring insert with ruby ball Ø4mm
- Probe holder elbow Ø 8mm
- Setting gage
- User's manual
- Test certificate





### FREE Swiss Pocket Knife with Purchase!

NEW!

| V3                           | J54-192-340                           | J54-192-370      |  |
|------------------------------|---------------------------------------|------------------|--|
| Measuring Range              | 16"/407mm                             | 28"/711mm        |  |
| Range with Probe inverted    | 20"/508mm                             | 31.9"/812mm      |  |
| Max. Permissible Errors      | 0.00032"/0.008mm                      | 0.00032"/0.008mm |  |
| Repeatability (2s)           | 0.00008"/0.002mm (Ø 0.00016"/0.004mm) |                  |  |
| Frontal Squareness Deviation | 0.0004"/0.010mm                       | 0.0006"/0.015mm  |  |
| Resolution                   | 0.00005"/0.001n                       | nm               |  |
| Measuring Force (N)          | 0.75 / 1.5                            |                  |  |
| Battery Life (Hrs)           | 40                                    |                  |  |
| Interfaces                   | USB/RS232                             |                  |  |
| Air Cushion                  | NO                                    |                  |  |

| +              |
|----------------|
| Swiss Quality! |

| V4                           | J54-191-440                           | J54-191-470     |  |
|------------------------------|---------------------------------------|-----------------|--|
| Measuring Range              | 16"/407mm                             | 28"/711mm       |  |
| Range with Probe inverted    | 28.3"/719mm                           | 40.2"/1023mm    |  |
| Max. Permissible Errors      | 0.0002"/0.005mm                       | 0.00028"/7mm    |  |
| Repeatability (2s)           | 0.00008"/0.002mm (Ø 0.00016"/0.004mm) |                 |  |
| Frontal Squareness Deviation | 0.0004"/0.010mm                       | 0.0006"/0.015mm |  |
| Resolution                   | 0.00005"/0.001mm                      |                 |  |
| Measuring Force (N)          | 0.75 / 1.5                            |                 |  |
| Battery Life (Hrs)           | 40                                    |                 |  |
| Interfaces                   | USB/RS232                             |                 |  |
| Air Cushion                  | YES                                   |                 |  |

| F          | -owler   |  |
|------------|----------|--|
| 11111      |          |  |
| WILLIAM ST | 5        |  |
|            |          |  |
| Ę          | IVE YEAR |  |
| ٧          | ARRANTY  |  |

| Order No.   | Description        | Range     | List Price |
|-------------|--------------------|-----------|------------|
| J54-192-340 | NEW V3 Height Gage | 16"/407mm | \$4543.00  |
| J54-192-370 | NEW V3 Height Gage | 28"/711mm | 4888.00    |
| J54-191-440 | NEW V4 Height Gage | 16"/407mm | 5980.00    |
| J54-191-470 | NEW V4 Height Gage | 28"/711mm | 6889.00    |

# **HEIGHT GAGES**

## HI GAGE ONE

The Sylvac measuring system is exceptionally fast (60" per second traverse) and is the most reliable and maintenance free system ever created for measurement

- · True inch/metric conversion
- Resolution: .0005"/.01mm
- Repeatability: .0004"/10µm
  Base size: 5.6" wide x 6.8" length
  Accuracy .0016"/.002"
- · Includes scriber/measuring probe
- · Direct RS-232 output
- · Scale not affected by oil, dust, chips, magnetism, shock, etc.








\*Receive a FREE 8mm Ball Probe with Purchase!

Order No. Range **List Price** Sale Price J54-212-016-1 16"/400mm \$1385.00 \$1250.00 J54-212-024-1 24"/600mm 1725.00 1399.00



# HI CAL HEIGHT GAGE

- Extra low measuring force, from 0.2N
- · Measurement of internal and external diameters, centerlines, heights, widths, depths, surfaces
- MIN/MAX/TIR capability
- · Excellent repeatability thanks to the motorized car-
- · Intuitive functions/minimizes key strokes
- · Great mobility
- High reliability
- Data output USB and RS-232
- Battery life: 40 hours rechargeable during operation Touch sensitive probe speed for easy operation
- Base with small footprint











| Order No.   | Range     | Accuracy         | List Price | Sale Price |
|-------------|-----------|------------------|------------|------------|
| J54-931-150 | 6"/150mm  | .00013"/.0034 μm | \$4437.00  | \$4037.00  |
| J54-931-300 | 12"/300mm | .00016"/.0042 μm | 5099.00    | 4699.00    |

# **QUICK CHECK**

**Multi-Function Check Standard** 





- · One compact, multi-function, precise standard
- Can be used to check and verify a multitude of measuring instruments
- Checks calipers, micrometers, depth gages, bore gages, test and dial indicators, caliper gages, height gages, protractors, combination sets and more
- Supplied with a manufacturer's test certificate and fitted wood case
- · All sizes marked are actual

| Order No.   | Description                                   | List Price | Sale Price |
|-------------|---|------------|------------|
| J53-813-015 | NEW Quick Check Multi-Function Check Standard | \$1490.00  | \$1375.00  |


NEW!

# LARGE SQUARE GAGE BLOCKS



· NIST Traceable

- Vertically more stable then rectangular blocks
- · Large sizes help eliminate block stacks
- Meets or exceeds Federal Specifications ASME B89.1.9-2002




# LONG RECTANGULAR GAGE BLOCKS









· Fowler's long gage blocks are rectangular in shape, Grade Ø and supplied with an NIST certificate

· Stackable using holding clamps

J53-670-777 holding clamp set used for holding two large blocks together

|             |                                    | •          |            |
|-------------|------------------------------------|------------|------------|
| Order No.   | Description                        | List Price | Sale Price |
| J53-675-216 | 5" Gage Block                      | \$156.80   | \$141.00   |
| J53-675-218 | 6" Gage Block                      | 190.40     | 171.00     |
| J53-675-220 | 7" Gage Block                      | 218.40     | 196.00     |
| J53-675-222 | 8" Gage Block                      | 246.40     | 221.00     |
| J53-675-224 | 10" Gage Block                     | 280.00     | 252.00     |
| J53-675-226 | 12" Gage Block                     | 296.80     | 267.00     |
| J53-675-228 | 16" Gage Block                     | 347.20     | 312.00     |
| J53-675-230 | 20" Gage Block                     | 442.40     | 398.00     |
| J53-670-008 | 8 piece Gage Block Set             | 1572.50    | 1415.00    |
| J53-670-777 | Holding Clamp for two large blocks | 92.95      | 83.00      |

# **SETTING MASTERS**

Fowler's Setting Masters are quick, easy and extremely accurate. Each comes with a manufacture's certificate of calibration and a wood case. Save time and money by calibrating your own measuring tools.

#### Depth Micrometer Checker J53-813-005

- · Ideal for quick, easy calibration and zero setting of depth micrometers
- Range: 0-6"
- · Graduation: 1"
- Accuracy: ± .000120"
- Reference block: 1" ± .000020"





#### Caliper/Height Gage Checker J53-813-010

- · Horizontal and vertical use
- Used for the calibration of height gages and calipers
  Scale on one side reads: 0.5", 2", 4", 6", 8", 10" and 12"
- for inside caliper measurements
- Scale on side reads: 1", 2", 4", 6", 8", 10" and 12" for height gage and caliper checking
- Accuracy: ± .0002"

| Order No.   | Range                           | List Price | Sale Price |
|-------------|---------------------------------|------------|------------|
| J53-813-005 | 6" Depth Micrometer Checker     | \$1450.00  | \$1350.00  |
| J53-813-010 | 12" Caliper/Height Gage Checker | 1545.00    | 1445.00    |

### **BORE GAGE SETTING MASTER KIT -Inch & Metric**

Fowler's Bore Gage Setting Master Kit is used for accurately setting any bore gage up to 6"/150mm in diameter to an accuracy of .0001"/.003mm



#### **Each Set includes:**

#### Setting Device

- Base anvil: 2.750" x .80"
- Adjustable anvil 2.375" x .375" (two each)
- Internal capacity: 6"/150mm
- · Depth capacity: 1"/25mm
- Centralizer capacity width: 2.625"/66.7mm
- · Quick-release holder for fast adjustment
- · Can also be used for external setting, depending on application (external mics, snap gages, caliper

#### Economy Gage Block Sets Inch model:

- · 36 piece
- Tolerances to .00005"
- · Certificate of Calibration to N.I.S.T.

#### Metric model:

- · 33 piece
- AS-2 grade
- Certificate of Calibration to N.I.S.T.

| Order No.   | Description                         | List Price | Sale Price |
|-------------|-------------------------------------|------------|------------|
| J53-646-000 | Inch Bore Gage Setting Master Kit   | \$275.00   | \$198.95   |
| J53-646-010 | Metric Bore Gage Setting Master Kit | \$295.00   | \$259.80   |

#### CALIPER, MICROMETER, SNAP GAGE CHECKING SET

Fowler's setting master is quick, easy and extremely accurate. It comes with a certificate of calibration and a fitted aluminum case. Save time and money by calibrating your own measuring tools quickly and easily.

#### Set Includes:

- Calibration certification traceable to N.I.S.T. standards
- · Stand height: 12.5"
- · 9 pc. Grade AS-0 gage block set (sizes: .625", .100", .125", .200", .250", .300", .500", 1.000" & 2.000"
- · Certificate of calibration is traceable to N.I.S.T. standards & provides the individual deviation of each block
- Optical flat (flatness: .000004"; Parallelism: .00002")



| Order No.     | Description   | List Price | Sale Price |
|---------------|---|------------|------------|
| J53-813-001-1 | Complete caliper, Micrometer and Snap Gage Checking Set | \$303.21   | \$272.37   |
| J53-813-002-0 | Mic Checker Holder without Blocks                       | 145.00     | 119.00     |

# **CYLINDRICAL SQUARES**



- Used for checking squares, height gages and other instruments
- Hardened and the ends are lapped to 90° angular accuracy
- 6" cylindrical squares: ±.0001"
- 12" cylindrical square: ±.00015"
- · Includes handles and wood case



| Order No.   | Description                | List Price | Sale Price |
|-------------|----------------------------|------------|------------|
| J52-750-006 | NEW 6" cylindrical square  | \$175.00   | \$160.00   |
| J52-750-012 | NEW 12" cylindrical square | 250.00     | 230.00     |

# SHOP-BLOX® RECTANGULAR GAGE BLOCK SETS

- Manufactured to meet N.I.S.T. Federal Specification ASME B89. 1.9 - 2002 tolerances on length for inch gage blocks
- Certificate of Calibration traceable to N.I.S.T.
- Tolerances to ±.00005"
- · In high-quality fitted wood case





| Order No.   | Description                                 | List Price | Sale Price |
|-------------|---|------------|------------|
| J53-672-036 | 36 piece Economy Rectangular Gage Block Set | \$275.00   | \$145.50   |
| J53-672-081 | 81 piece Economy Rectangular Gage Block Set | 484.00     | 310.50     |

# GRADE Ø RECTANGULAR STEEL GAGE BLOCK SETS

- · Grade Ø
- Each block certified to N.I.S.T.
- · Each block is individually serialized
- · Sizes clearly marked on each block
- · Complete with fitted wooden case





J53-670-038

| Order No.   | Description                                 | List Price | Sale Price |
|-------------|---|------------|------------|
| J53-670-038 | 36 piece Grade Ø Rectangular Gage Block Set | \$434.55   | \$231.00   |
| J53-670-080 | 81 piece Grade Ø Rectangular Gage Block Set | 799.70     | 510.00     |

# X-TENDED RANGE

# **PIN GAGE SETS**

Minus and Plus Tolerances

Ideal for checking hole size, location, gage slots, distance between holes, go/no-go gaging and setting other gages and micrometers.



#### in one set! .011"—.060" & .061"—.250"

#### Features:

- · Class ZZ
- Black oxide finish offers extra protection against corrosion and rust, promotes longer life, and highlights wear trends that enables calibration to be performed more effectively
- 240 pcs
- · Range: 0.011" 0.250" in .001" increments.
- · Set includes 2 handles and our X-Glide all
- purpose teflon lubricant
- Certificate of accuracy traceable to N.I.S.T. and registered ISO 9001

| Order No.   | Description        | Accuracy         | List Price | Sale Price |
|-------------|--------------------|------------------|------------|------------|
| J53-880-823 | Plus Pin Gage Set  | +0.0002"-0.0000" | \$229.95   | \$209.95   |
| J53-880-833 | Minus Pin Gage Set | +0.0000"-0.0002" | 229.95     | 209.95     |

### **PIN GAGE HANDLES**



- 8 sizes cover a full range of pin gages (.011" 1.0")
  Color coded handle for GO, NO/GO applications
- Both handle and collets are made of aluminum for pin protection
- Collets are spring loaded and self-centering

| Order No.   | Description              | List Price | Sale Price |
|-------------|--------------------------|------------|------------|
| J53-885-000 | NEW .011"—.060"          | \$17.00    | \$14.50    |
| J53-885-001 | NEW .061"—.250"          | 20.00      | 16.50      |
| J53-885-002 | NEW .251"—.500"          | 23.50      | 20.50      |
| J53-885-003 | NEW .501"—.625"          | 27.00      | 24.00      |
| J53-885-004 | NEW .626"—.750"          | 33.00      | 30.00      |
| J53-885-005 | NEW .751"—.832"          | 36.00      | 33.00      |
| J53-885-006 | NEW .833"—.916"          | 40.00      | 37.00      |
| J53-885-007 | NEW .917"—1.0"           | 45.00      | 41.00      |
| J53-885-008 | NEW All Sizes .011"—1.0" | 230.00     | 210.00     |

# **DIAL CALIBRATION TESTER**



- · Use for calibration of dial and test indicators as well as cylinder bore gages
- · Measuring travel 1"/25mm
- Non rotating anvil
- Large micrometer drum for fine and precise adjustment
- · Can be used vertically or horizontally
- Provides direct comparative measurements
- Repeatability 0.000012"/0.0003mm when used with Sylvac probe system (54-618-500 & 54-618-148)
- Can also be used with a high accuracy, high resolution electronic dial indicator (54-530-156) with 8mm mounting stem
- Robust construction
- Includes clamps and holders for various gages and a magnifying lens for stress free reading of dial gages.

| Order No.   | Description                 | List Price | Sale Price |
|-------------|-----------------------------|------------|------------|
| J53-520-000 | NEW Dial Calibration Tester | \$4064.50  | \$2435.00  |

# **DIAL CALIPERS**

# MIUM DIAL CALIPER



0.001"

\$112.20

\$78.50

### MACHINIST GRADE DIAL CALIPERS

**NEW** 0-6"



- .001"/.02mm reading dial face
- · Tough shockproof gearing


J52-008-006-2

· Supplied in shop-hardened case

| Order No.   | Range                  | Dial Face<br>Color | List<br>Price | Sale<br>Price |
|-------------|------------------------|--------------------|---------------|---------------|
| J52-008-704 | 0-4"                   | White              | \$51.50       | \$41.20       |
| J52-008-714 | 0—4"                   | Black              | 51.50         | 41.20         |
| J52-008-706 | 0—6"                   | White              | 70.50         | 54.20         |
| J52-008-707 | 0—6"                   | Black              | 70.50         | 54.20         |
| J52-008-709 | 0-150mm (Metric Model) | Yellow             | 70.50         | 54.20         |
| J52-008-708 | 0—8"                   | White              | 88.40         | 66.20         |
| J52-008-712 | 0-12"                  | White              | 117.05        | 89.60         |

# **DIAL CALIPERS**

# **HEAVY DUTY DIAL CALIPERS**



| Order No.   | Range       | Jaw Length | List Price | Sale Price |
|-------------|-------------|------------|------------|------------|
| J52-025-108 | 8" Caliper  | 2.5"       | \$128.25   | \$86.50    |
| J52-025-112 | 12" Caliper | 2.875"     | 186.50     | 129.50     |

# 0-6" DIAL CALIPERS



- .100" per revolution
- · Dial graduation: .001"
- · Accuracy: ±.001"
- · Hardened stainless steel rack
- · Supplied in shop-hardened case

| Dial Face   |       | List    | Sale    |
|-------------|-------|---------|---------|
| Order No.   | Color | Price   | Price   |
| J52-008-007 | White | \$84.55 | \$33.50 |
| J52-008-005 | Black | 84.55   | 33.50   |

# **EXTENDED RANGE DIAL CALIPERS**



| Order No.   | Range       | Depth of Jaws | List Price | Sale Price |
|-------------|-------------|---------------|------------|------------|
| J52-008-018 | 18" Caliper | 3.125"        | \$232.90   | \$178.20   |
| J52-008-024 | 24" Caliper | 3.375"        | 282.25     | 221.20     |

#### Poly-Cal® **ELECTRONIC CALIPER** Inch/Metric/Fraction



- · Range 6"/150mm
- Polycarbonate frame
- Large easy-to-read display Resolution .0005"/.01mm
- (Fractions by 1/64" increments)
- Absolute/Incremental Measurement
- · Direct inch/metric/fraction conversion
- 4-way measuringAccuracy +/-.008"
- · Supplied with clip-on vinyl pouch

| Order No.   | Description                 | List Price | Sale Price |
|-------------|-----------------------------|------------|------------|
| J54-101-175 | Poly-Cal Electronic Caliper | \$24.60    | \$19.50    |
| J54-100-350 | CR2032 Battery              | 5.50       |            |

### 4" thru 12" ECONOMY DIGITAL CALIPERS



- Ceramic capacitive sensor
- · Stainless steel frame
- Direct Inch/Metric conversion
  Accuracy: .001"/.02mm (4" & 6" models)
- .0015"/.04mm (8" & 12" models)
   Resolution: .0005"/.01mm
   Large easy-to-read LCD display
- Absolute referencing
- Includes molded case

| Order No.     | Range               | List Price | Sale Price |
|---------------|---------------------|------------|------------|
| J54-100-004-2 | 0-4"/100mm Caliper  | \$94.10    | \$75.60    |
| J54-100-000-2 | 0-6"/150mm Caliper  | 109.75     | 80.40      |
| J54-100-008-2 | 0-8"/200mm Caliper  | 128.80     | 101.20     |
| J54-100-112-2 | 0-12"/300mm Caliper | 168.00     | 137.80     |
| J54-100-350   | CR2032 Battery      | 5.50       |            |

### **WATER RESISTANT IP54 ELECTRONIC CALIPERS**



- · Water resistant to IP54 specifications
- Stainless steel frame
- Direct Inch/Metric conversion Accuracy: .001"/.02mm (6" models)
- Resolution: .0005"/.01mm
- Absolute referencing
  Large easy-to-read LCD display
  4-way measurement
- Includes molded case

| Order No.     | Range                               | List Price | Sale Price |
|---------------|-------------------------------------|------------|------------|
| J54-100-777-2 | 0-6"/150mm Electronic IP54 Caliper  | \$123.20   | \$95.20    |
| J54-100-712-2 | 0-12"/300mm Electronic IP54 Caliper | 179.20     | 141.30     |
| J54-100-350   | CR2032 Battery                      | 5.50       |            |

### PRO-MAX ELECTRONIC CALIPER



RS232

- · Maximum Error: .001"/.02mm
- · 4-way measurement, inside, outside, depth and step
- Resolution: .0005"/.01mm
- Repeatability: .0005"/.01mm
- Range: 6"/150mm
- Direct inch/metric conversion
- Temperature range 5 to 40C° working; -20 to 60C° in storage
- Hardened stainless steel construction
- RS-232 output
- · Features Absolute/Relative Measur
  - ing Modes Hold function
- · Includes molded case

| Order No.     | Range                                 | List Price | Sale Price |
|---------------|---------------------------------------|------------|------------|
| J54-200-777-1 | 0-6"/150mm Pro-Max Electronic Caliper | \$157.00   | \$119.00   |
| J54-100-350   | CR2032 Battery                        | 5.50       |            |

RESISTANT

# TRA-VALUE CAL ELECTRONIC CALIPERS



J54-100-350

J54-101-150-2

- Accuracy: .001"/.02mm (6" models)
- Stainless steel frame
- Large easy-to-read display
  Resolution: .0005"/.01mm
- Direct inch/metric conversion
- Absolute/Incremental Measurement
- 4-way measuringIncludes molded case

CR2032 Battery



5.50

t Also available with a Super Large Display with Hold Feature!

| Order No.     | Range     | Display Type                          | List Price | Sale Price |
|---------------|-----------|---------------------------------------|------------|------------|
| J54-101-150-2 | 6"/150mm  | Regular Display                       | \$45.00    | \$31.80    |
| J54-101-600-1 | 6"/150mm  | Super Large Display with hold feature | 56.00      | 37.50      |
| J54-101-200-1 | 8"/200mm  | Regular Display                       | 67.20      | 56.50      |
| J54-101-800-1 | 8"/200mm  | Super Large Display with hold feature | 84.00      | 63.50      |
| J54-101-300-1 | 12"/300mm | Regular Display                       | 90.00      | 88.60      |
| J54-101-900-1 | 12"/300mm | Super Large Display with hold feature | 110.00     | 83.40      |

# **EURO-CAL**

### **ELECTRONIC CALIPERS**



| Order No.     | Description                              | Accuracy      | List Price | Sale Price |
|---------------|--|---------------|------------|------------|
| J54-100-330-1 | 6"/150mm Euro-Cal IV Electronic Caliper  | .±.001"/.02mm | \$111.95   | \$76.30    |
| J54-100-331   | 8"/200mm Euro-Cal IV Electronic Caliper  | ±.001"/.02mm  | 132.50     | 95.60      |
| J54-100-332   | 12"/300mm Euro-Cal IV Electronic Caliper | ±.0015"/.03mm | 170.00     | 126.30     |
| J54-100-350   | CR2032 Battery                           |               | 5.50       |            |

# TRA-RANGE ELECTRONIC CALIPERS



- · Hold feature
- Preset mode now includes
- offset for inside jaws
- All sizes feature fine adjustment screw
- · Resolution: .0005"/.01mm
- Inch/metric conversion
- · Includes molded case
- .500" internal measuring nibs





| Order No.     | Range                | Jaw Depth | Accuracy    | List Price | Sale Price |
|---------------|----------------------|-----------|-------------|------------|------------|
| J54-100-312   | 0-12"/300mm Caliper  | 3.5"      | .002"/.04mm | \$193.75   | \$159.50   |
| J54-100-024-1 | 0-24"/600mm Caliper  | 4"        | .003"/08mm  | 282.25     | 239.40     |
| J54-100-042-1 | 0-40"/1000mm Caliper | 4.9"      | .004"/10mm  | 1170.35    | 649.00     |
| J54-100-350   | CR2032 Battery       |           |             | 5.50       |            |

### **ULTRA-CAL III HEAVY DUTY ELECTRONIC CALIPERS**

Heavy Duty Ultra-Cal III, made in Germany, combines the Swiss-patented Sylvac non-contact inductive measuring system with output capabilities.





NEW!

| Order No.   | Length of<br>Bottom Jaws | Length of<br>Top Jaws |
|-------------|--------------------------|-----------------------|
| J54-100-012 | 3.2"                     | 1.5"                  |
| J54-100-020 | 5.9"                     | 2.25"                 |
| J54-100-212 | 3.2"                     | 1.3"                  |

- · Inside, outside measurements only
- Fine adjustment
- Resolution: .0005"/.01mm
- Repeatability" .0005"/.01mm ±2s
- · Incremental floating zero
- Direct inch/metric conversion
- · Fast tracking speed of approximately 60"/second
- · Combination zero/data/hold button
- · Hold feature freezes display for later viewing
- · Direct RS232C output
- Frame and jaws are precision ground of hardened stainless steel

Save 10%



J54-100-012



| Range             | Overall Accuracy  | List Price  | Sale Price   |
|-------------------|---|---|--|
|                   |   |   |  |
| NEW 0-12"/0-300mm | .0015"/.04mm  | \$968.00  | \$868.00   |
| NEW 0-20"/0-500mm | .002"/.05mm   | 1584.00   | 1200.00  |
|                   |   |   |  |
| NEW 0-12"/0-300mm | .0015"/.04mm  | \$1122.00   | 1000.00  |
| RS232 Opto Cable  |   | 119.00  |  |
|                   | NEW 0-12"/0-300mm<br>NEW 0-20"/0-500mm<br>NEW 0-12"/0-300mm | NEW 0-12"/0-300mm .0015"/.04mm<br>NEW 0-20"/0-500mm .002"/.05mm<br>NEW 0-12"/0-300mm .0015"/.04mm | NEW 0-12"/0-300mm         .0015"/.04mm         \$968.00           NEW 0-20"/0-500mm         .002"/.05mm         1584.00           NEW 0-12"/0-300mm         .0015"/.04mm         \$1122.00 |

# **EZ-ID/OD ELECTRONIC GAGE**





Direct RS232 outputIncludes wooden case

### ULTRA-LITE MARK III ELECTRONIC CALIPERS

Fowler's Ultra-Lite Mark III Electronic Calipers offer many advantages over conventional calipers. Featuring a low weight that improves measuring results. Measuring pressure control for improved repeatability. For increased wear resistance, jaw faces are titanium-coated on hardened steel.



#### Features:

- · Internal and external measurements with two presets.
- Min/Max functions.
- · Hold feature freezes display for later viewing.
- · Menu customizable with free software
- · Incremental floating zero.
- Measuring Speed = 60"/1.5m per second.
- Large, high-contrast LCD display indicates in/mm, hold and zero functions.
- New low drain, high efficiency lithium wafer battery—4500 hrs. of continuous
- · Direct inch/metric conversion.
- Direct RS232C output connects tool to any computer or printer without an
- · Special application accessories available.
- · Includes case

#### Specifications:

- External Jaws: Length = 6"(150mm);
- thickness = .28" (7mm); material: titanium coated stainless steel.
   Internal Pins: Length = .71" (18mm)
- diameter of nibs = .2" (5mm); material = tungsten carbide.







| Order No.   | Range        | Accuracy              | Repeatability         | Weight                       | List Price | Sale Price |
|-------------|--------------|-----------------------|-----------------------|------------------------------|------------|------------|
| J54-110-312 | 0-12"/300mm  | 0.0012"/30 <i>µ</i> m | 0.0008"/20 <i>µ</i> m | 2.4 lb./1.1 kg               | \$1950.00  | \$1750.00  |
| J54-110-324 | 0-24"/600mm  | 0.0016"/40µm          | 0.0008"/20µm          | 2.9 lb./1.3 kg               | 2275.00    | 2075.00    |
| J54-110-340 | 0-40"/1000mm | 0.0024"/60 <i>μ</i> m | 0.0008"/20 <i>µ</i> m | 3.5 lb./1 <mark>.6 kg</mark> | 2720.00    | 2520.00    |

# **MICROMETERS**

# 0.5" OUTSIDE MICROMETER



- 0-.5" micrometer by .001", satin chrome finish
- Forged steel frame
- Anvil and spindle hardened and precision ground with microlapped ends.
- Clear, crisp graduations on barrel and thimble
- · Diameter of measuring faces: .0197"
- Parallelism: .00005"
- Flatness: .00003"
- Includes case

| Order No.   | Range          | List Price | Sale Price |
|-------------|----------------|------------|------------|
| J52-230-000 | 05" micrometer | \$29.35    | \$20.00    |

#### **OUTSIDE MICROMETERS**

with Decimal Equivalents on Frame





- Black decimal equivalents on satin chrome finished forged steel frame
- · Graduations: .0001"
- · Ratchet thimble and locking nut
- Includes case

| Order No.     | Range | List Price            | Sale Price |
|---------------|-------|-----------------------|------------|
| J52-235-001-1 | 0-1"  | \$5 <mark>2.65</mark> | \$30.80    |
| J52-235-002-2 | 1-2"  | 63.85                 | 40.30      |
| J52-235-003-2 | 2-3"  | 7 <mark>6.15</mark>   | 51.40      |

### **SWISS-STYLE MICROMETERS**



- .0001" reading
- · Carbide measuring faces
- · Insulated frame
- Ratchet thimble and locking nut
- Microfine graduations
- Sizes over 1" include standard
- Meets or exceeds Federal specifications
- · Includes case

| Range | List Price                           | Sale Price   |
|-------|--------------------------------------|--|
| 0-1"  | \$39.15                              | \$23.50  |
| 1-2"  | 45.85                                | 31.25  |
| 2-3"  | 56.55                                | 36.40  |
| 3-4"  | 64.90                                | 41.30  |
| 4-5"  | 80.10                                | 48.60  |
| 5-6"  | 94.10                                | 59.80  |
|       | 0-1"<br>1-2"<br>2-3"<br>3-4"<br>4-5" | 0-1" \$39.15<br>1-2" 45.85<br>2-3" 56.55<br>3-4" 64.90<br>4-5" 80.10 |

# **DIGIT COUNTER MICROMETERS**



- Digital counter reads to .001".
- Resolution: .0001" (using vernier)
- · Microfine graduations on satin chrome
- · Carbide tipped measuring faces
- · Positive locking nut on spindle
- · Sizes over 1" include standard
- · Includes case

| Order No.   | Range | List Price | Sale Price |
|-------------|-------|------------|------------|
| J52-224-001 | 0-1"  | \$88.40    | \$43.50    |
| J52-224-002 | 1-2"  | 92.90      | 55.25      |
| J52-224-003 | 2-3"  | 105.85     | 61.30      |
| J52-224-004 | 3-4"  | 116.40     | 67.00      |

### Micrometer Calibration Set is available on page 6!

# **MICROMETERS**

# XTRA-VALUE II ELECTRONIC MICROMETERS

Jet black, grey enamel finishLarge LCD display.

• Resolution: .00005"/.001mm

Accuracy: ±.00016"/.004mm (up to 2")Direct RS-232 output

· Carbide measuring faces.

· Absolute and incremental modes

· Ratchet thimble

· Includes shop hardened case



| Order No.   | Description                             | Range        | List Price | Sale Price |
|-------------|---|--------------|------------|------------|
| J54-870-001 | Xtra-Value II Electronic Micrometer     | 0-1"/0-25mm  | \$84.00    | \$59.50    |
| J54-870-002 | Xtra-Value II Electronic Micrometer     | 1-2"/25-50mm | 85.00      | 75.40      |
| J54-870-003 | Xtra-Value II Electronic Micrometer     | 2-3"/50-75mm | 99.95      | 89.80      |
| J54-870-103 | Xtra-Value II Electronic Micrometer Set | 0-3"/0-75mm  | 260.00     | 183.00     |
| J54-100-350 | CR2032 Battery                          |              | 5.50       |            |

### **ELECTRONIC COOLANT RESISTANT MICROMETERS**

- Protected to IP54 specifications
- · Large LCD Display
- Automatic switch off
- Resolution: .00005"/.001mm
- · Direct RS-232 output
- Carbide measuring faces
- · Absolute & incremental modes
- Sizes over 1"/25mm include standard



| Order No.     | Description                    | Range          | List Price | Sale Price |
|---------------|--------------------------------|----------------|------------|------------|
| J54-860-001-1 | IP54 Electronic Micrometer     | 0-1"/0-25mm    | \$106.40   | \$79.20    |
| J54-860-002-1 | IP54 Electronic Micrometer     | 1-2"/25mm-50mm | 123.20     | 89.20      |
| J54-860-003-1 | IP54 Electronic Micrometer     | 2-3"/50mm-75mm | 134.40     | 99.80      |
| J54-860-103-1 | IP54 Electronic Micrometer Set | 0-3"/0-75mm    | 350.00     | 259.70     |
| J54-100-350   | CR2032 Battery                 |                | 5.50       |            |

# XTRA MAG MAG BASE MICROMETER STAND



- Holds standard 0-12" micrometers firmly to metal surfaces
- · Use at machine centers, work, assembly and inspection stations, steel tables and shelves
- · V-bottom for mounting on cylindrical surfaces
- · On/Off magnet switch
- Blue enamel finish
- Base is 2.30" L x 1.20" W x 3.50" H



| Order No.   | Description                        | List Price | Sale Price |
|-------------|------------------------------------|------------|------------|
| J52-247-010 | NEW Xtra-Mag Base Micrometer Stand | \$48.50    | \$40.00    |
|             |                                    |            |            |

# ADJUSTABLE MICROMETER STAND



A compact, well-constructed, folding micrometer stand with a unique locking mechanism that positions the micrometer over a 180° range for perfect use and viewing.

| Order No.   | Description      | List Price | Sale Price |
|-------------|------------------|------------|------------|
| J52-247-005 | Micrometer Stand | \$33.05    | \$23.50    |

# **MICROMETER SETS**

# TRA-VALUE II ELECTRONIC MICROMETER SET



- · Protected to IP54 specifications
- · Large LCD Display
- Automatic switch off
- Resolution: .00005"/.001mm
- · Direct RS-232 output
- Carbide measuring faces
- Absolute & incremental modes

Sizes over 1"/25mm include standard

Complete in a

"Shop Hardened"
molded case!



| Order No.   | Description                           | List Price | Sale Price |
|-------------|---------------------------------------|------------|------------|
| J54-870-103 | 0-3"/0-75mm Electronic Micrometer Set | \$260.00   | \$183.00   |

### **SWISS STYLE MICROMETER SETS**



- .0001" reading (.01mm on metric set)
- Carbide measuring faces
- · Ratchet thimble and locking nut
- Microfine graduations
- · Sizes over 1" include standard
- · Meets or exceeds Federal specifications

Complete in a 
"Shop Hardened" 
molded case!

| Order No.   | Range       | List Price | Sale Price |
|-------------|-------------|------------|------------|
| J52-229-213 | 0-3" set    | \$141.10   | \$99.50    |
| J52-229-214 | 0-4" set    | 217.30     | 121.50     |
| J52-229-220 | 0-100mm set | 217.30     | 121.50     |

### **DIGIT COUNTER MICROMETER SETS**



- · Digital counter reads to .001".
- · Resolution: .0001" (.01mm on metric set)
- · Microfine graduations on satin chrome.
- · Carbide tipped measuring faces
- Database libratella
- · Ratchet thimble
- · Positive locking nut on spindle
- · Sizes over 1" supplied with standards

Complete in a 
"Shop Hardened" 
molded case!

| Order No.   | Range      | List Price | Sale Price |
|-------------|------------|------------|------------|
| J52-224-103 | 0-3" set   | \$294.00   | \$182.00   |
| J52-224-104 | 0-4" set   | 399.85     | 201.80     |
| J52-224-220 | 0-75mm set | 294.00     | 182.00     |

# **MICROMETER SETS**

# 12 PIECE OUTSIDE INCH MICROMETER SET



Fowler micrometers are of the finest quality available, at prices that defy competition. Special care in design and workmanship create a long lasting precision tool.

#### Features:

- · Hammertone blue baked enamel finish
- Microfine graduations on satin chrome finish and carbide tipped measuring faces
- Diameter of measuring faces: .256"
- Graduation: .0001"
- Flatness: .00003"
- · Quick, easy zero adjustment on sleeve
- · Positive lever locking clamp
- Spindle thread hardened, ground and lapped for ultimate accuracy
- Anvil & spindle hardened and precision ground with microlap finish on tips
- Meets or exceeds Federal accuracy specs
- Includes adjustment wrenches and fitted wooden case for all 12 micrometers





NEW!

All in a fitted wooden case!

| Order No.     | Description              | List Price | Sale Price |
|---------------|--------------------------|------------|------------|
| J52-215-012-1 | NEW 0-12" Micrometer Set | \$891.50   | \$578.00   |

# **DEPTH MICROMETERS**

# **ECONOMY DEPTH MICROMETERS**






- · Satin chrome finish
- · Base surface hardened, ground & lapped
- Ratchet thimble
- Locking clamp.001" GraduationRod diameter: .176"
- · Includes shop-hardened case.

| Order No.   | Range | Graduation | Base | List Price | Sale Price |
|-------------|-------|------------|------|------------|------------|
| J52-225-110 | 0-4"  | .001"      | 2.5" | \$112.60   | \$99.80    |
| J52-225-112 | 0-6"  | .001"      | 2.5" | 136.80     | 122.60     |
| J52-225-114 | 0-4"  | .001"      | 4"   | 119.30     | 107.00     |
| J52-225-116 | 0-6"  | .001"      | 4"   | 142.50     | 136.50     |

### DIGIT COUNTER DEPTH MICROMETERS

- · Easy-to-read digit counter
- · Microfine .001" graduations
- · 4" base constructed of tool steel, hardened and ground
- · Satin chrome finish
- · Ratchet thimble
- Locking clamp
- · Rod diameter: .176"
- · Includes wrench and fitted case



| Order No.   | Range | Graduation | Base | List Price | Sale Price |
|-------------|-------|------------|------|------------|------------|
| J52-225-176 | 0-6"  | .001"      | 2.5" | \$141.05   | \$132.00   |
| J52-225-226 | 0-6"  | .001"      | 4"   | 152.90     | 140.00     |

## **IP54 ELECTRONIC DEPTH MICROMETERS**





- · Resolution: .00005"/.001mm
- Range: 0—6"/150mm
  Hardened tool steel, precision ground and microlapped 4" base
- · Rod diameter: .176"
- Protected to IP54 standards · Automatic switch off
- · Large LCD display
- · Includes fitted case



| Order No.   | Description                            | List Price | Sale Price |
|-------------|--|------------|------------|
| J54-225-456 | 0-6"/150mm Electronic Depth Micrometer | \$199.90   | \$162.95   |
|             | ·                                      |            |            |

# **DEPTH GAGES**



# PROOF 0-22" DIAL DEPTH GAGE with IP54 protection!



- · 0-1" AGD Group 2 IP54 Indicator
- · Sealed bezel, top cap and dial with bellows on stem
- · Sealed back plate
- .001" graduations
- · 4" base ground and lapped for flatness
- Rods connect for 22" capacity
- · Includes 2 extra points (spline & needle)
- Tolerance markers





### All in a shop-hardened case!

| Order No.   | Description            | List Pice | Sale Price |
|-------------|------------------------|-----------|------------|
| J52-125-007 | NEW X-Proof Depth Gage | \$185.00  | \$122.00   |

# X-DEPTH 22 0-22" DEPTH GAGE

#### Twice the range of competitive products!

- 0−1" travel indicator
- .001" Graduations
- · Rods connect together for full 22" capacity
- · Satin chrome finish
- · Base size: 4"
- · Includes 2 extra points for small hole applications: one 0.078" dia. x 1" long and one needle point x 1" long
- · Includes shop-hardened case



| Order No.     | Description      | List Price | Sale Price |
|---------------|------------------|------------|------------|
| J52-125-006-1 | 0-22" Depth Gage | \$170.25   | \$101.20   |



- · 0-1" travel electronic indicator
- · Zero reset at any position
- · On/off button
- · Relative/absolute measuring
- Bottom surface of the base is hardened. ground & lapped
- Full 22" range Resolution .0005"/.01mm
- · Hold feature
- · Includes 2 extra points for small hole applications; one 0.078" dia. x 1" long and one needle point x 1" long
- · Includes shop-hardened case

| Order No.   | rder No. Description        |          | Sale Price |
|-------------|-----------------------------|----------|------------|
| J54-125-777 | 0-22" Electronic Depth Gage | \$229.55 | \$158.20   |

# **INDICATING MICROMETERS**



# INDI-X INDICATING MICROMETERS



- · Anvil and spindle hardened and precision ground
- · Fully insulated frame, satin chrome finish
- · Wider Micro-Fine graduations
- Carbide tipped anvil & spindle
- · Retracting button conveniently located in relation to operator's hand
- 0-1" Range, head graduated in .001"
- · Flatness: .000012'
- Dial graduated in .00005"
- Indicated accuracy of .00015"
- · Diameter of spindle: .256"
- Includes case

| Order No.   | Description                       | List Price | Sale Price |
|-------------|-----------------------------------|------------|------------|
| J52-245-501 | 0-1" Indi-X Indicating Micrometer | \$291.20   | \$245.00   |
| J52-245-502 | 1-2" Indi-X Indicating Micrometer | 343.85     | 315.00     |

### **ELECTRONIC INDICATING MICROMETERS**

A superior tool in quality and design, the Fowler/Bowers Electronic indicating Micrometer operates quickly and easily.







- · Retractable anvil travel: .275"(7mm)
- Non-rotating spindle
- · Switchable resolution
- 0.0005"/0.00005" (0.01/0.001mm)
   Repeatability: 0.00005"(1µm)
- Measuring force 4.5—6N
- · Carbide tipped measuring faces
- · Adjustable table for part
- · Two reference memories
- · Preset Recall function
- · Hold/freeze display function
- · Direct inch/metric conversion
- Tolerance indication
- · Min/Max/TIR function
- · Bidirectional RS-232 output.
- · Includes case.

| Order No.   | Description           | List Price | Sale Price |
|-------------|-----------------------|------------|------------|
| J54-245-777 | 0 - 1.25"/0-30mm      | \$1150.00  | \$1050.00  |
| J54-245-780 | 1.25" - 2.50"/30-60mm | 1365.00    | 1265.00    |

# **INSIDE MICROMETERS**



**RANGE: .2" to 2.2"!** 



# Includes setting ring!

- · Range: .2-2.2"
- · Satin chrome finish on barrel and thimble
- · Microfine graduations (.001") on a satin chrome finish permit easy reading
- Accuracy: ±.0002" (.005mm)

| • | Ratchet | stop | thim | bl |
|---|---------|------|------|----|

- Easy zero adjustment on the sleeve
- Meets or exceeds Federal accuracy specs
- · Includes a setting ring
- Includes a spanner wrench and a fitted case

| Order No.   | Description       | Range     | List Price | Sale Price |
|-------------|-------------------|-----------|------------|------------|
| J52-275-005 | Inside Micrometer | .2 - 2.2" | \$146.70   | \$121.50   |

# **ELECTRONIC IP54 INSIDE MICROMETER**



- · Measuring jaws & faces fully hardened & microlapped for accuracy.
- · Each gage includes appropriate setting ring.
- Water Resistant to IP54 specifications.
- True inch/metric conversion
- Resolution: .00005"/.001mm
- · Large easy-to-read LCD display
- Friction thimble
- · Includes case.

| Order No.   | Description | List Price | Sale Price |
|-------------|-------------|------------|------------|
| J54-860-275 | .2 - 1.2"   | \$211.70   | \$180.00   |
| J54-860-276 | 1 - 2"      | 229.55     | 195.00     |

## INSIDE MICROMETERS

- · Each set consists of an inside micrometer head and a series of fully hardened and lapped extension rods of different lengths all with carbide measuring faces
- · Anvil and spindle are hardened and precision ground with microlap finish on ends.
- · Spindle thread hardened, ground & lapped.
- · Microfine graduations on satin chrome.
- · Positive locking nut on spindle.
- · It is recommended that the inside micrometer with a rod be calibrated by a micrometer or ring gage.
- · Coiled spring pressure contact type rods are each marked with appropriate length.
- · Quick, easy zero adjustment on the sleeve.
- Accuracy = .00005" x (3 + L"/2)
- · Meets or exceeds Federal accuracy specs.
- Reference standard included with set.
- Includes a wrench and a case



J52-243-212-1

| Order No.     | Range   | Graduation | List Price | Sale Price |
|---------------|---------|------------|------------|------------|
| J52-243-026-1 | 2 - 6"  | 0.001"     | \$116.50   | \$89.00    |
| J52-243-212-1 | 2 - 12" | 0.001"     | 141.10     | 119.00     |
| J52-243-220-1 | 2 - 20" | 0.001"     | 186.50     | 144.00     |



Fowler-Bowers XTH Holematic Pistol Grip range of bore gages offer extended travel with fixed anvils. The pistol grip handle incorporates a constant measuring pressure to eliminate operator "feel."



### Fastest Measuring System! **Ergonomic Design!** Amazing Repeatability!

- · Large easy-to-read swivel display
- Self centering heads
- RS-232C output and USB connectivity
- Three preset memories
- Fixed anvils
- Resolution: .00005" /.001mm Range .080"—12" (2—300mm)
- Tungsten carbide measuring faces on all 3-point heads from .5" (12.5mm) and up.
- Heads with special anvils available for threads, splines, slots, etc.
   Sizes over .500" (12.5mm) feature blind bore capability
- Setting rings included in all sets
   Includes UKAS certificates for all pistol grip, heads and rings
- Special anvils available





Contact the Fowler Technical Department for special anvil applications.

# **BORE GAGES**

| Electronic H | Electronic Holematic Pistol Grip XTH - Individual sizes (includes pistol grip, head and ring) |                   |                             |            |            |  |
|--------------|---|-------------------|-----------------------------|------------|------------|--|
| Order Number | Range   | Accuracy          | Depth                       | List Price | Sale Price |  |
|              |   | 2-Point Heads     |                             |            |            |  |
| J54-566-701  | .080"100" (2-2.5mm)   | .00015" (0.004mm) | .350" (9 <mark>mm)</mark>   | \$2841.00  | \$2272.80  |  |
| J54-566-702  | .100"120" (2.5-3mm)   | .00015" (0.004mm) | .350" (9 <mark>mm)</mark>   | 2841.00    | 2272.80    |  |
| J54-566-703  | .120"160" (3-4mm)   | .00015" (0.004mm) | .470" ( <mark>12mm)</mark>  | 2841.00    | 2272.80    |  |
| J54-566-704  | .160"200" (4-5mm)   | .00015" (0.004mm) | .700" ( <mark>18mm)</mark>  | 2841.00    | 2272.80    |  |
| J54-566-705  | .200"250" (5-6mm)   | .00015" (0.004mm) | .700" ( <mark>18mm)</mark>  | 2841.00    | 2272.80    |  |
|              |   | 3-Point Heads     |                             |            |            |  |
| J54-566-706  | .250"312" (6-8mm)   | .00015" (0.004mm) | 2.28" (58mm)                | \$2070.00  | \$1656.00  |  |
| J54-566-708  | .312"375" (8-10mm)  | .00015" (0.004mm) | 2.28" (58mm)                | 2036.00    | 1628.80    |  |
| J54-566-710  | .375"500" (10-12.5mm)   | .00015" (0.004mm) | 2.28" (58mm)                | 2144.00    | 1715.20    |  |
| J54-566-712  | .500"625" (12.5-16mm)   | .00015" (0.004mm) | 2.44" ( <mark>62mm)</mark>  | 2172.00    | 1737.60    |  |
| J54-566-716  | .625"750" (16-20mm)   | .00015" (0.004mm) | 2.44" ( <mark>62mm)</mark>  | 2302.00    | 1841.60    |  |
| J54-566-720  | .750"-1" (20-25mm)  | .00015" (0.004mm) | 2.62" (66mm)                | 2467.00    | 1973.60    |  |
| J54-566-725  | 1-1.375" (25-35mm)  | .00015" (0.004mm) | 2.62" (66mm)                | 2915.00    | 2332.00    |  |
| J54-566-735  | 1.375"-2" (35-50mm)   | .00015" (0.004mm) | 3.15" ( <mark>80mm)</mark>  | 2739.00    | 2191.20    |  |
| J54-566-740  | 2-2.625" (50-65mm)  | .00020" (0.005mm) | 3.15" ( <mark>80mm)</mark>  | 2807.00    | 2245.60    |  |
| J54-566-745  | 2.625"-3.250" (65-80mm)   | .00020" (0.005mm) | 3.15" ( <mark>80mm)</mark>  | 2807.00    | 2245.60    |  |
| J54-566-750  | 3.250"-4" (80-100mm)  | .00020" (0.005mm) | 3.35" ( <mark>85mm)</mark>  | 2989.00    | 2391.20    |  |
| J54-566-800  | 4-5" (100-125mm)  | .00025" (0.006mm) | 3.94" ( <mark>100mm)</mark> | 3131.00    | 2504.80    |  |
| J54-566-825  | 5-6" (125-150mm)  | .00025" (0.006mm) | 3.94" ( <mark>100mm)</mark> | 3323.00    | 2658.40    |  |
| J54-566-850  | 6-7" (150-175mm)  | .00030" (0.007mm) | 3.94" ( <mark>100mm)</mark> | 3527.00    | 2821.60    |  |
| J54-566-875  | 7-8" (175-200mm)  | .00030" (0.007mm) | 3.94" ( <mark>100mm)</mark> | 3669.00    | 2935.20    |  |
| J54-566-876  | 8-9" (200-225mm)  | .00030" (0.008mm) | 3.94" ( <mark>100mm)</mark> | 4673.00    | 3738.40    |  |
| J54-566-877  | 9-10" (225-250mm)   | .00030" (0.008mm) | 4.05" ( <mark>103mm)</mark> | 5160.00    | 4128.00    |  |
| J54-566-878  | 10-11" (250-275mm)  | .00035" (0.009mm) | 4.05" ( <mark>103mm)</mark> | 5342.00    | 4273.60    |  |
| J54-566-879  | 11-12" (275-300mm)  | .00035" (0.009mm) | 4.05" ( <mark>103mm)</mark> | 5897.00    | 4717.60    |  |



# Extra Handles 25% off (with set purchase)

Holematic XTH Pistol Grip Only

| Order No.   | Range               | List Price              | Sale Price |
|-------------|---------------------|-------------------------|------------|
| J54-556-350 | .080"250" (2-6mm)   | \$19 <mark>51.00</mark> | \$1450.00  |
| J54-556-375 | .250"750" (6-20mm)  | 19 <mark>51.00</mark>   | 1450.00    |
| J54-556-400 | .750"-4" (20-100mm) | 19 <mark>51.00</mark>   | 1450.00    |
| J54-556-480 | 4"-12" (100-300mm)  | 19 <mark>51.00</mark>   | 1450.00    |

















| Com | olete | Range | Sets |
|-----|-------|-------|------|
|     |       |       |      |

| Order No.         | Range                    | Includes                              | List Price | Sale Price |
|-------------------|--------------------------|---------------------------------------|------------|------------|
| J54-566-009       | .080"250" (2-6mm)        | 5 heads, 1 handle, 3 rings            | \$6431.00  | \$5144.00  |
| J54-566-010       | .250"375" (6-10mm)       | 2 heads, 1 handle, 1 ring             | 2524.00    | 2019.00    |
| J54-566-020       | .375"750" (10-20mm)      | 3 heads, 1 handle, 2 rings            | 2977.00    | 2381.00    |
| J54-566-050       | .750"-2" (20-50mm)       | 3 heads, 1 handle, 2 rings            | 3901.00    | 3120.00    |
| J54-566-100       | 2-4" (50-100mm)          | 3 heads, 1 handle, 2 rings            | 4321.00    | 3456.00    |
| J54-566-105       | 4-6" (100-150mm)         | 2 heads, 1 handle, 1 ring             | 3901.00    | 3120.00    |
| J54-566-110       | 6-8" (150-200mm)         | 2 heads, 1 handle, 1 ring             | 5212.00    | 4169.00    |
| J54-566-200       | 4-8" (100-200mm)         | 4 heads, 1 handle, 2 rings            | 8352.00    | 6681.00    |
| J54-566-210       | .750"-4" (20-100mm)      | 6 heads, 1 handle, 4 rings            | 6431.00    | 5144.00    |
| J54-566-620       | .250"750" (6-20mm)       | 5 heads, 1 handle, 3 rings            | 3589.00    | 2871.00    |
| Connectivity Kits |                          | · · · · · · · · · · · · · · · · · · · |            |            |
| Order No.         | Description              |                                       |            |            |
| J54-115-444       | RS232 Power Computer Cor | nnect Kit                             | 157.00     |            |
| J54-115-528       | USB Power Computer Conne | ect Kit                               | 220.00     |            |
| J54-100-350       | CR2032 Battery           |                                       | 5.50       |            |

# **BORE GAGES**

# **DIAL BORE GAGE SETS** with Carbide Anvils

#### Carbide anvils

- · Easy-to-read
- Economical
- Graduation: .0005"
- · Chrome plated handle
- Insulated grip

Order No.

J52-646-100

.152-646-300

· Includes extension holder and fitted case





J52-646-100

Range

.7 - 1.5'

2-6"

**List Price** Sale Price \$139.10 114.95

## **EXTENDER 1.4" TO 6" OR 35mm TO 160mm DIAL BORE GAGE SETS** with Carbide Anvils

Description

Dial Bore Gage Set

Dial Bore Gage Set

Industry's two most popular bore gage ranges combined in one set!



103.20

#### Carbide Anvils

- Easy-to-read
- Economical
- · Graduation: .0005" or .01mm
- · Insulated grip
- · 1.4" to 6" range or 35 to 160mm
- · Chrome plated handle
- · Includes extension holder and fitted case





| Order No.   | Description                   | List Price | Sale Price |
|-------------|-------------------------------|------------|------------|
| J52-646-400 | Inch X-Tender Bore Gage Set   | \$174.80   | \$124.60   |
| J52-646-220 | Metric X-Tender Bore Gage Set | 193.15     | 135.20     |

## **EXTENDER-E ELECTRONIC 1.4" TO 6" DIAL BORE GAGE SET**

Γ€ND€R∙

Industry's two most popular bore gage ranges combined in one easy-to-use ELECTRONIC set!

All the same benefits included in the X-Tender Dial Bore Gage are now available with an electronic indicator providing inch/metric reading capability. Preset size of master for absolute reading and minimum hold feature to lock on the bore size as the gage is rocked in the part to be measured.



#### **Bore Gage Features:**

- · Range: 1.4"-6"/35mm-150mm
- Carbide anvils
- Easily adjustable
- Self-centering
- Includes extension holder
- Shop hardened case

#### Indicator Features:

- · Dual reading inch/metric electronic indicator
- Bar graph and numeric digital display
- Resolution: .00005"/.001mm
- · Preset with recall
- ABS/INC measurement
- Min/Max/TIR

Includes FREE Instructional CD!



For instructional video search "X-tender Bore Gage" at www.youtube.com

| Order No.   | Description             | List Price | Sale Price |
|-------------|-------------------------|------------|------------|
| J54-646-401 | XTender-E Bore Gage Set | \$301.90   | \$265.80   |
| J54-100-350 | CR2032 Battery          | 5.50       |            |

# **ID - OD MEASURING**

# XTRA-VALUE INTERNAL & EXTERNAL ELECTRONIC CALIPER GAGES



- Robust housing
- Large LCD display
- Reading: .01"/.1mm/1/64ths Accuracy: .01"/.3mm/1/64ths Battery: CR2032

J54-554-730

Spring loaded with locking nut



INCH • METRIC • FRACTION

| Order No.   | Description          | Range       | List Price | Sale Price |
|-------------|----------------------|-------------|------------|------------|
| J54-554-630 | Outside Caliper Gage | 0-6"/150mm  | \$44.25    | \$36.20    |
| J54-554-730 | Inside Caliper Gage  | .5-6"/150mm | 44.25      | 36.20      |
| J54-100-350 | CR2032 Battery       |             | 5.50       |            |


# **INTERNAL & EXTERNAL ELECTRONIC CALIPER GAGES**



J54-554-711

- · Easy to hold
- Rugged housing
- · Large, LCD display
- Resolution: .0002"/.005mm
- Accuracy: ±.0008"/±.02mm
- Preset capability
- · Direct inch/metric conversion
- · Absolute/Incremental measurements
- · High-impact, aircraft aluminum case





| Metric  | Inch     | L    | s     | Н     | Tip Radius |
|---------|----------|------|-------|-------|------------|
| 5-15mm  | 0.2-0.6" | 20mm | 1.0mm | 1.5mm | 0.3mm      |
| 5-25mm  | 0.2-1.0" | 35mm | 1mm   | 1.5mm | 0.3mm      |
| 10-30mm | 0.4-1.2" | 55mm | 2mm   | 3.5mm | 0.5mm      |
| 20-40mm | 0.8-1.6" | 80mm | 3mm   | 6.5mm | 0.5mm      |
| 30-50mm | 1.2-2.0" | 80mm | 3mm   | 8.5mm | 0.5mm      |

Dimensions for External Caliners

| Metric  | Inch     | L    | S     | Н    | Tip Radius |
|---------|----------|------|-------|------|------------|
| 0-10mm  | 0-0.4"   | 40mm | 3mm   | 8mm  | 0.5mm      |
| 0-20mm  | 0-0.8"   | 80mm | 6.5mm | 25mm | 0.75mm     |
| 10-30mm | 0.4-1.2" | 80mm | 6.5mm | 25mm | 0.75mm     |
| 20-40mm | 0.8-1.6" | 80mm | 6.5mm | 25mm | 0.75mm     |
| 30-50mm | 1.2-2.0" | 80mm | 6.5mm | 25mm | 0.75mm     |

#### **Internal Caliper Gages**

| Order No.   | Range              | List Price | Sale Price |
|-------------|--------------------|------------|------------|
| J54-554-611 | .200"—.590"/5-15mm | \$162.35   | \$141.20   |
| J54-554-622 | .200"-1"/5-25mm    | 174.15     | 151.40     |
| J54-554-623 | .400"-1.2"/10-30mm | 185.85     | 162.40     |
| J54-554-624 | .790"-1.6"/20-40mm | 185.85     | 162.40     |
| J54-554-625 | 1.2"-2"/30-50mm    | 185.85     | 162.40     |
| J54-100-350 | CR2032 Battery     | 5.50       |            |

#### **External Caliper Gages**

| Order No.   | Range              | List Price | Sale Price |
|-------------|--------------------|------------|------------|
| J54-554-711 | 0400"/0-10mm       | \$162.35   | \$141.20   |
| J54-554-722 | 0790"/0-20mm       | 174.15     | 151.40     |
| J54-554-723 | .4"-1.2"/10-30mm   | 185.85     | 162.40     |
| J54-554-724 | .790"-1.6"/20-40mm | 185.85     | 162.40     |
| J54-554-725 | 1.2"-2"/30-50mm    | 185.85     | 162.40     |
| J54-100-350 | CR2032 Battery     | 5.50       |            |



No Gimmicks No Hurdles No Nonsense We are so confident that these Fowler/Sylvac products are the most accurate, most dependable, best made products you can buy, we are extending the warranty to last a lifetime!

Quality, accuracy, dependability, world-class customer service and now a real Lifetime Warranty!

# **MARK VI ELECTRONIC INDICATORS**

- Robust construction
- · Water and coolant resistant
- Protection class IP-67
- · Repeatability: 2µm
- Output: Proximity/Power -USB/RS232/digimatic/Wireless
- Battery life: 10,000 hours of operation
- · Menus customizable with free software
- Wide range of functions (MIN/MAX/DELTA, TOL, Factor, Preset. Auto Off, etc)
- Aluminum housing
- Bezel rotates 270°
- · Large display with LED tolerance indicators
- Includes lug back













J54-530-135\*

common functions



\*Available with Bluetooth, contact the Fowler Technical Department for details.

| Order No.    | Description  | Maximum Error   | Resolution      | List Price | Sale Price |
|--------------|--------------|-----------------|-----------------|------------|------------|
| J54-530-125  | 0500"/12.5mm | 0.0004"/.01mm   | 0.0005"/.01mm   | \$410.00   | \$355.00   |
| J54-530-135* | 0500"/12.5mm | 0.00012"/.003mm | 0.00005"/.001mm | 510.00     | 475.00     |
| J54-530-145  | 0-1"/25mm    | 0.0004"/.01mm   | 0.0005"/.01mm   | 468.00     | 410.00     |
| J54-530-155* | 0-1"/25mm    | 0.00016"/.004mm | 0.00005"/.01mm  | 560.00     | 515.00     |



### **ULTRA-CAL V ELECTRONIC CALIPERS**

Top-of-the-line Caliper! Fowler's BEST Caliper! J54-100-067-1 Ultra Cal V ROXIMITY INTERFACE All Models are available with Bluetooth,

- Maximum Error: .001"/.02mm
- · 4-way measurement, inside, outside, depth and step. (6" & 8" models)
- Resolution: .0005"/.01mm
  Repeatability: .0005"/.01mm
- · Direct inch/metric conversion
- Temperature range 5 to 40°C working; -20 to 60°C in storage
- · Hardened stainless steel construction
- · Direct RS-232 output
- Features Absolute/Relative Measuring Modes
- · Hold function

contact the Fowler Technical Department for details.

- Thumbroll (6" model only)
- Includes case

| Order No.     | Description | Accuracy              | Resolution    | List Price | Sale Price |
|---------------|-------------|-----------------------|---------------|------------|------------|
| J54-100-067-1 | 6"/150mm    | 0.0008"/20μm          | 0.0005"/.01mm | \$189.00   | \$150.00   |
| J54-100-068-1 | 8"/200mm    | 0.0012"/30 $\mu$ m    | 0.0005"/.01mm | 450.00     | 390.00     |
| J54-100-069-1 | 12"/300mm   | 0.0012"/30 <i>µ</i> m | 0.0005"/.01mm | 540.00     | 490.00     |

## **RAPID-MIC ELECTRONIC MICROMETERS**



- Auto On/Off
- · Position recall
- · IP67 with or without data cable.
- · Delrin quick displacement thimble
- Adjustable measuring force, 5N/10N Menu customizable with free software
- Non-rotating spindle
- USB output
- · Carbide anvils
- Extended Range 0-30mm, 30-66mm and 66-102mm
- · Blade anvils and speciality micrometers are available, contact Fowler Technical Department.





J54-815-111



\*Available with Bluetooth, contact the Fowler Technical Department for details.

| Order No.    | Description        | Max Error       | List Price | Sale Price |
|--------------|--------------------|-----------------|------------|------------|
| J54-815-030* | 0-1.18"/0-30mm     | 0.00012"/.003mm | \$490.00   | \$425.00   |
| J54-815-060  | 1.18"-2.6"/30-66mm | 0.00016"/.004mm | 725.00     | 680.00     |
| J54-815-100  | 2.6"-4.0"/66-102mm | 0.00020"/.005mm | 1014.00    | 915.00     |
| Set          |                    |                 |            |            |
| J54-815-111  | 0-4"/0-102mm       |                 | 2240.00    | 1975.00    |

# XTEST X-TEST INDICATOR

TWICE the range of most indicators!

- · Jeweled movement
- · Revolution counter
- · Easy-to-read tilted dial
- Automatic reversal
- 210° Swivel arc5/32" stem
- Tungsten carbide point: .080"
- Range: .060" inch model
- · Range: 1.6mm metric model





Contact Points

| J52-562-002 |
|-------------|
|             |

| Order No.   | Description      | Graduations | Dial Diameter | Dial Reading         | List Price | Sale Price |
|-------------|------------------|-------------|---------------|----------------------|------------|------------|
| J52-562-001 | X-Test Indicator | .0005"      | 1-1/2"        | 0-15-0               | \$117.55   | \$109.95   |
| J52-562-002 | X-Test Indicator | .0005"      | 1"            | 0-15-0               | 117.55     | 109.95     |
| J52-562-003 | X-Test Indicator | .001"       | 1"            | 0-15-0               | 117.55     | 109.95     |
| J52-562-007 | X-Test Indicator | .01mm       | 25mm          | 0-40 <mark>-0</mark> | 117.75     | 109.95     |
| J52-562-008 | X-Test Indicator | .01mm       | 38mm          | 0-40 <mark>-0</mark> | 117.75     | 109.95     |

XTEST VERTICAL X-TEST INDICATOR

## TWICE the range of most indicators!

- Range: .060"
- Dial reading: 0-15-0
- Jeweled movement
- · Revolution counter
- · Easy-to-read tilted dial
- Automatic reversal
- · 210° Swivel arc
- 5/32" stem
- Tungsten carbide point: .080"







J52-562-004

| Order No.   | Description               | Graduations | Dial Diameter | List Price | Sale Price |
|-------------|---------------------------|-------------|---------------|------------|------------|
| J52-562-004 | Vertical X-Test Indicator | .0005"      | 1-1/2"        | \$128.75   | \$109.95   |
| J52-562-005 | Vertical X-Test Indicator | .0005"      | 1"            | 128.75     | 109.95     |
| J52-562-006 | Vertical X-Test Indicator | .001"       | 1"            | 128.75     | 109.95     |

# XTEST INDICATOR & ACCESSORY COMBO KIT

#### Each Combo Kit Includes:

- · X-Test Dial Test Indicator (see above)
- · Axial support
- · Height gage bar with clamp
- Adaptor sleeve: 5/32" to 3/8"
- · Contact point case
- · Contact point wrench
- · Complete in "Shop Hardened" case.







| Order No.   | Description              | Graduations | List Price | Sale Price |
|-------------|--------------------------|-------------|------------|------------|
| J52-562-100 | 52-562-001 w/accessories | .0005"      | \$172.65   | \$155.40   |
| J52-562-110 | 52-562-002 w/accessories | .0005"      | 172.65     | 155.40     |
| J52-562-120 | 52-562-003 w/accessories | .001"       | 172.65     | 155.40     |
|             |                          |             |            |            |

### **TEST INDICATORS**

All Fowler Test Indicators include bi-directional constant clockwise rotation, automatic reversal, three dovetail mountings, jeweled movement, two dovetail clamps and a molded case.



| Order<br>No. | Face<br>Color | Total<br>Range | Dial<br>Reading | Graduation | Dial<br>Diameter | Point<br>Length | List<br>Price | Sale<br>Price |
|--------------|---------------|----------------|-----------------|------------|------------------|-----------------|---------------|---------------|
| J52-562-774  | white         | .030"          | 0-15-0          | .001"      | 1"               | 1/2"            | \$105.30      | \$62.80       |
| J52-562-778  | black         | .030"          | 0-15-0          | .0005"     | 1"               | 1/2"            | 111.95        | 62.80         |
| J52-562-775  | white         | .030"          | 0-15-0          | .0005"     | 1"               | 1/2"            | 111.95        | 62.80         |
| J52-562-776  | white         | .030"          | 0-15-0          | .0005"     | 1-1/2"           | 1/2"            | 117.05        | 68.80         |
| J52-562-780  | black         | .030"          | 0-15-0          | .0005"     | 1-1/2"           | 1/2"            | 117.05        | 68.80         |



| Order       | Face  | Total | Dial    |            | Dial     | Point  | List     | Sale    |
|-------------|-------|-------|---------|------------|----------|--------|----------|---------|
| No.         | Color | Range | Reading | Graduation | Diameter | Length | Price    | Price   |
| J52-563-770 | white | .008" | 0-4-0   | .0001"     | 1"       | 1/2"   | \$111.95 | \$90.40 |
| J52-563-771 | black | .008" | 0-4-0   | .0001"     | 1"       | 1/2"   | 111.95   | 90.40   |
| J52-563-777 | white | .008" | 0-4-0   | .0001"     | 1-1/2"   | 1/2"   | 111.95   | 90.40   |
| J52-563-772 | black | .008" | 0-4-0   | .0001"     | 1-1/2"   | 1/2"   | 115.30   | 90.40   |



| Order       | Face  | Total | Dial    |            | Dial     | Point   | List     | Sale    |
|-------------|-------|-------|---------|------------|----------|---------|----------|---------|
| No.         | Color | Range | Reading | Graduation | Diameter | Length  | Price    | Price   |
| J52-562-781 | white | .020" | 0-10-0  | .0005"     | 1"       | 1-7/16" | \$115.30 | \$87.20 |
| J52-562-782 | black | .020" | 0-10-0  | .0005"     | 1"       | 1-7/16" | 115.30   | 87.20   |
| J52-562-783 | white | .020" | 0-10-0  | .0005"     | 1-1/2"   | 1-7/16" | 115.30   | 87.20   |
| J52-562-784 | black | .020" | 0-10-0  | .0005"     | 1-1/2"   | 1-7/16" | 115.30   | 87.20   |

### **ULTRATAST TEST INDICATORS**

#### Horizontal Test Indicators

- · Box-type housing opens on one side only.
- Bottom and side walls are one piece construction which encloses and protects the movement from shocks and damage.
- · Self-contained movement
- Jeweled movement bearings, precision gears and pinions for maximum sensitivity and accuracy
- · Satin-chrome finish is corrosion proof
- · Stylus: ball diameter .080"/2mm
- Swivel range 220° on all models
- Includes 1/4" & 5/16" Dovetail clamps





Save \$40.00 or more on all Models!

| J52- | 568. | 200 |
|------|------|-----|

| A   | IE | 1/1 | /! |
|-----|----|-----|----|
| _ ' |    |     |    |

| Order No.   | Reading | Measiuring<br>Range | Dial<br>Diameter | Stylus<br>Length | Measuring<br>Force |
|-------------|---------|---------------------|------------------|------------------|--------------------|
| J52-568-005 | .0005"  | ±.015"              | 1.083"           | .453"            | 0.15N              |
| J52-568-010 | .0005"  | ±.015"              | 1.50"            | .453"            | 0.15N              |
| J52-568-015 | .0001"  | ±.004"              | 1.50"            | .453"            | 0.15N              |
| J52-568-022 | .0005"  | ±.015"              | 1.083"           | 1.417"           | 0.07N              |

| Order No.   | Description                             | List Price | Sale Price |
|-------------|---|------------|------------|
| J52-568-005 | NEW UltraTast Horizontal Test Indicator | \$121.00   | \$80.00    |
| J52-568-010 | NEW UltraTast Horizontal Test Indicator | 137.50     | 90.00      |
| J52-568-015 | NEW UltraTast Horizontal Test Indicator | 176.00     | 120.00     |
| J52-568-022 | NEW UltraTast Horizontal Test Indicator | 196.90     | 130.00     |



### **Unmatched versatility and ease!**

# **MULTIMODE ELECTRONIC TEST INDICATOR**

Fowler's QuadraTest offers unrivaled measuring versatility in an Electronic Test Indicator.

· 4 Measuring Resolutions!

|            | Smallest |
|------------|----------|
| Resolution | Division |
| 0400       | .0005"   |
| 0400       | .00005"  |
| 0-1-0      | 0.01mm   |
| 0—1—0      | 0.001mm  |

• 4 Measuring Modes!

Min, Max, TIR and Direct

- · True Inch/Metric conversion
- · Water, oil and coolant resistant to IP65!
- 1-1/2" diameter dial face rotates a full 360°
- · Bar graph and numeric digital display
- Meets or exceeds DIN/ISO Standards Maximum error on .00005" scale at full range: .0004"
- ..080" contact ball diameter

J54-562-888





J54-562-777



| Order No.   | Contact Point Length | List Price | Sale Price |
|-------------|----------------------|------------|------------|
| J54-562-777 | 1/2"                 | \$210.00   | \$190.00   |
| J54-562-888 | 1-7/16"              | 310.00     | 289.00     |
| J54-115-528 | Power USB Cable      | 220.00     |            |
| J54-100-350 | CR2032 Battery       | 5.50       |            |

### **TEST INDICATOR KIT with Universal Holder**

### with Certificate of Calibration

- · Auto-reverse.
- · Jeweled movement.
- · Range: .030'
- Graduation: .0005"
- · Dial reading: 0-15-0
- Dial diameter: 1.125"

Carbide contact points.

· Point length: .400"




J52-565-200





 Includes .080" & .040" contact points, Universal clamp, height gage attachment, 3/8" & 1/4" dovetail clamps in a fitted molded case



\*\*\* To receive your free Universal Holder, please fax your proof of purchase to Fowler at: (617) 630-5139

| Order No.   | Description           | List Price | Sale Price |
|-------------|-----------------------|------------|------------|
| J52-562-999 | Test Indicator Kit    | \$112.15   | \$102.50   |
| XTRA MAG    | A VERSATILE UNIVERSAL | & MAG BASI | Е СОМВО    |

- 2 universal ball sockets
- · Microfine adjustment screw
- · 3-9/16" extension arm
- Dovetail mounting

#### Test Indicator: (J52-562-778)

- · Range: .030"
- Reading: 0-15-0
- · Jeweled movement · Graduation: .0005"
- · Auto-reversing · .080" diameter point





as a Universal Base! 040"& .120

Virtually unlimited positioning

J52-568-005

#### All complete in a shop-hardened case!

| Order No.   | Description                  | List Price | Sale Price |
|-------------|------------------------------|------------|------------|
| J52-585-105 | Xtra Mag only                | \$51.70    | \$37.80    |
| J52-585-100 | Xtra Mag with Test Indicator | 155.10     | 107.80     |

# XTRA-SURF SURFACE GAGE

### with a built-in Switchable Magnetic Base




Magnetic Base











- · Set includes 3-1/8" x 2-1/16" permanent magnetic base with on/off switch, fine adjustment on base and a 5/16" x 9" upright
- .0005" test indicator No. J52-562-778 (see page 31) with .040", .080" & .120" contact points
- · Swivel clamp to mount indicator
- Two dovetail stems: 5/32" & 3/8"
- · A 4" hardened scriber
- · Form fitted shop-hardened case for easy accessibility and storage

| Order No.   | Description                 | List Price | Sale Price |
|-------------|-----------------------------|------------|------------|
| J52-155-747 | Xtra-Surf                   | \$213.40   | \$122.50   |
| J52-155-743 | Xtra-Surf without indicator | 105.85     | 91.50      |





#### Features:

- · All accept 3/8" indicators
- Mag base and HOLD-TEC with fine adjust also accepts 8mm indicators
- · All have dovetail clamps for test indicators
- Mag base features 2 fine adjusts making it 6-Axis Mag Base
- HOLD-TEC can be mounted in drill chucks, collets, dial gage stands with 8mm mount diameter to make a quick transfer stand
- · Mag base has 180 lb. pull
- · Adjust to any position
- · Powerful On/Off mag base
- · Central locking system

| Order No.   | Description                                   | List Price | Sale Price |
|-------------|---|------------|------------|
| J52-585-085 | NEW HOLD-Tec Mag Base with Double Fine Adjust | \$147.30   | \$125.00   |
| J52-565-036 | NEW HOLD-Tec without Fine Adjust              | 82.70      | 75.00      |
| J52-565-038 | NEW HOLD-Tec with Fine Adjust                 | 89.90      | 80.00      |



**ELECTRONIC INDICATORS** 



- Direct Inch/Metric Conversion
   IP54 Coolant & fluid resistant
- Auto Off feature
- 2-1/4" dial face
- 3/8" stem 4-48 thread
- Resolution .00005"/.001mm
- Accuracy: .00016"/.004mm (to 1")
- Tolerance indicators
- · Absolute/incremental reading
- · Lugback supplied on 1/2" model.
- · Lugbacks for 1" and 2" models, J52-525-605
- · Floating zero
- · Carbide tipped point



| Order No.   | Description   | List Price | Sale Price |
|-------------|---|------------|------------|
| J54-520-305 | .5"/12.5mm Indi-Max Electronic Indicator with point set | \$329.00   | \$279.30   |
| J54-520-310 | 1"/25mm Indi-Max Electronic Indicator with point set    | 369.00     | 319.20     |
| J54-520-320 | 2"/50mm Indi-Max Electronic Indicator with point set    | 479.00     | 429.60     |
| J54-100-350 | CR2032 Battery  | 5.50       |            |
| J54-520-399 | Absolute data cable                                     | 139.00     |            |

## **ELECTRONIC INDICATORS**

Now available in .5"/12.5mm & 1"/25mm ranges!

INCH • METRIC • FRACTION

- · Direct Inch/Metric Conversion
- Auto Off feature
- · 2-1/4" dial face
- · Lugback and 3/8" stem mountings
- · Resolution .0005"/.01mm
- Tolerance indicators
- Absolute/incremental reading
- Floating zero
- · Carbide tipped point









Low Cost, High Quality, **Multi-Function** J54-520-250 **Indicators** 

**Carbide-tipped point!** 

| Order No.   | Description   | List Price | Sale Price |
|-------------|---|------------|------------|
| J54-520-250 | 1"/25mm Indi-X Blue Electronic Indicator                            | \$94.00    | \$58.50    |
| J54-520-260 | 1"/25mm/64ths Indi-X Blue Inch-Metric-Fraction Electronic Indicator | 96.25      | 61.50      |
| J54-520-255 | .5"/12.5mm Indi-X Blue Electronic Indicator                         | 87.30      | 51.50      |

# X-PROOF IP54 SHOCKPROOF INDICATORS



#### Protection Includes:

- · Rubber bellows on stem
- O-ring seal on safety cap
- · O-ring protection for bezel and rotating dial
- · Sealed back plate

#### Specifications:

- · Robust, shockproof design
- Travel: 1"
- Reading: .001"
- Continuous reading: 0-100
- Tolerance markers
- · AGD Group 2, 2-1/4" dia. · Lugback and carbide point



| Order No.   | Description                 | List Pice | Sale Price |
|-------------|-----------------------------|-----------|------------|
| J52-520-450 | X-Proof Indicator—Whiteface | \$69.40   | \$29.80    |
| J52-520-455 | X-Proof Indicator—Blackface | 75.00     | 32.25      |

# **INDICATORS**

# CHROME FLEX MAG SET

with INDIXIDE Electronic Indicator or AGD Black face Indicator

Included Magnetic

Indicator Back for

mounting to most

metal surfaces!

#### Indi-X Blue Indicator features:

- · Direct Inch/Metric Conversion
- 1"/25mm travel
- Auto Off feature
- · 2-1/4" dial face
- Lugback and 3/8" stem mountings
- Resolution .0005"/.01mm
- Tolerance indicators
- Absolute/incremental reading
- Floating zero
- · Carbide tipped point



#### Flex Arm Mag Base features:

- · Corrosion resistant chrome plated flex arm
- · 85 lb. pull magnet
- Holds rigidly in almost any position
- · V-base for mounting on rounded surfaces

### Magnetic Indicator Back features:

 Use for positioning indicator on most metal surfaces

All in a shop-hardened case.

· Protective coating





#### AGD Indicator features:

- AGD Group 2
- · Dial diameter: 2-1/4"
- Travel: 1'
- · Reading: .001"
- · Continuous reading: .100" · Carbide tipped point

### See the Indi-X Blue on page 36!

| Order No.   | Description  | List Price | Sale Price |
|-------------|--|------------|------------|
| J54-585-100 | Chrome Flex Mag and Indi-X Blue Electronic Indicator Set | \$230.95   | \$125.00   |
| J52-585-500 | Chrome Flex Mag and AGD Black Face Indicator Set         | 173.25     | 123.00     |

### **FINE ADJUST MAG BASE SET** with INDIXIDE Electronic Indicator or AGD Black face Indicator

#### Indi-X Blue Indicator features:

- Direct Inch/Metric Conversion
- 1"/25mm travel
- Auto Off feature
- 2-1/4" dial face
- Lugback and 3/8" stem mountings
- Resolution .0005"/.01mm Tolerance indicators
- Absolute/incremental reading
- Floating zero
- Carbide tipped point

#### Magnetic Base features:

- 85 lb. pull
- · Fine adjustment.
- · V-bottom base

#### Magnetic Indicator Back features:

- Use for positioning the indicator on most metal surfaces.
- Protective coating

### All in a shop-hardened case.









### AGD Indicator features:

- AGD Group 2
- · Dial diameter: 2-1/4"
- Travel: 1
- · Reading: .001"
- Continuous reading: .100"
- · Carbide tipped point

See the Indi-X Blue on page 36!

| Order No.   | Description  | List Price | Sale Price |
|-------------|--|------------|------------|
| J54-585-075 | Fine Adjust Mag Base Set with Indi-X Blue Electronic Indicator Set | \$196.35   | \$145.00   |
| J52-585-125 | Fine Adjust Mag Base with AGD White Face Indicator Set             | \$150.15   | 70.00      |

# **INDICATORS**

# X-PROOF WATER RESISTANT INDICATOR SET



Order No.

J52-585-155

### **BEST VALUE!**

IP54 Shockproof indicator available!

### Magnetic Base (J52-585-010):

- On-Off lever release magnet
- Travel: 1'

- Tolerance markers
- AGD Group 2, 2-1/4" dia.
- · Lugback and carbide point

- O-ring protection for bezel

X-Proof Water Resistant Indicator Set

# All in a shop-hardened case.



Description

- · Fine adjustment
- Base dimensions: 2" x 2-11/32" x 1-13/16"
- Mounts test indicators with 1/4" post
- 85 lb. pull
- · V-base for placing on round surfaces
- X -Proof Indicator (J52-520-450):

- · Reading: .001"
- · Continuous reading: 0-100

- · Robust, shockproof design
- · Rubber bellows on stem
- · O-ring seal on safety cap
- and rotating dial
- · Sealed back plate

**List Pice** 

\$77.85



Sale Price

\$55.00



- Protective coating

### X-Proof IP54 Indicator features:

- Specifications:
- Robust, shockproof design
- Travel: 1" · Reading: .001"
- Continuous reading: 0-100
- Tolerance markers
- · AGD Group 2, 2-1/4" dia. · Lugback and carbide point

### **Protection Includes:**

- · Rubber bellows on stem.
- · O-ring seal on safety cap. O-ring protection for bezel
- and rotating dial · Sealed back plate
- All in a shop-hardened case.

| Order No.   | Description  | List Pice | Sale Price |
|-------------|--|-----------|------------|
| J52-585-450 | NEW Chrome Flex Mag and X-Proof Indicator Set —Whiteface | \$180.00  | \$129.00   |
| J52-585-455 | NEW Chrome Flex Mag and X-Proof Indicator Set —Blackface | 186.00    | 135.00     |

# **INDICATORS**



- 6" x 6" x 2" granite base Positive lock screw
- · Fine adjustment knob for zero setting
- · Microscrew fingertip control
- Flatness = .00005"

### X -Proof Indicator (J52-520-450):

- · Travel: 1"
- · Reading: .001"
- · Continuous reading: 0-100
- Tolerance markers
- · AGD Group 2, 2-1/4" dia.
- · Lugback and carbide point
- · Robust, shockproof design
- · Rubber bellows on stem · O-ring seal on safety cap
- · O-ring protection for bezel and rotating dial
- · Sealed back plate



| Order No.   | Description            | List Pice | Sale Price |
|-------------|------------------------|-----------|------------|
| J52-580-450 | NEW X-Proof Gage Stand | \$177.20  | \$115.00   |

## 12" WORKSHOP TRANSFER X-STAND

The Workshop Transfer Stand is compact in size and lightweight!

### Adjusts a variety of ways!



- · Overall height 12"
- · Revolutionary design
- · Large range fine adjustment
- · Perfect for applications where the stand is moved and/or needs to be transported from location to location
- · Hold test indicators or dial gages with dovetail holders & special adaptors
- · Large capacity positioning range
- Can be locked in any position
  Base 3" wide x 3.54" long
- Large handwheel provides fine adjustment
- Stainless steel construction
- · Packed in a high quality aluminum case
- Weight 4.8 lbs. (2.2 kg)



| Order No.    | Description                   | List Price | Sale Price |
|--------------|-------------------------------|------------|------------|
| .152-620-717 | 12" Workshop Transfer X-Stand | \$108.90   | \$89.95    |

# **PROTRACTORS**

# TRA-VALUE 9" ELECTRONIC LEVEL

Fowler's 9" Laser Level provides instant 4 x 90° digital inclination display. With embedded magnets on its measuring surface, a beamsplitter projects a 90° laser cross hair for leveling at-a-distance. It also includes a 1/4-20 mount for tripod use.

- Measuring range: 4 x 90°
- Resolution: .05

Order No.

- Accuracy: ±.2° Repeatability: ±.05
- Standard 9 volt battery (250 hou
- Dimensions: 9"L x 1"W x 2-1/4"
- Includes two-way level and plum
- Reversible reading for inverted in

### Xtra-Value 9" Electronic Level J54-440-600 III-MAG Protractor



**Dimensions:** L: 2.375" x W: 1.375" x H: 2.375"

The mini-MAG Protractor provides instant 360° digital inclination display of any angle with the additional unique feature of embedded magnets on both sides and the bottom which make it ideal for a variety of measurements.

- Embedded magnets with 3.5lb. pull
- Uses standard 9V battery (250 hrs.)

WLER HIGH

- Measuring range: 360° (4 x 90°)
- Display automatically inverts
- Resolution: .05°
- Accuracy: ±.2°
- Repeatability: .05°
- Hold feature



\$67.15

\$55.99

Display inverts for easy reading!

| Order No.     | Description         | List Price | Sale Price |
|---------------|---------------------|------------|------------|
| J54-422-450-1 | Mini-Mag Protractor | \$89.55    | \$69.50    |
|               |                     |            |            |

# Fowler Digi-Pro ELECTRONIC PROTRACTOR

The Digi-Pro electronic protractor includes embedded magnets for unique measurement areas. On/Off, Zero, Hold and Reverse feature to invert the display for easier reading in certain situations.

- Embedded 25 lb. pull magnets
- Full, 360° measuring range
- Accuracy: ±.2°
- Repeatability: ±.05°
- Resolution: .05°
- Invertible display feature
- Voltage: Standard 3V lithium battery



USE THE DIGI-PRO TO MAKE FAST AND ACCURATE ANGULAR MEASUREMENTS!

| Order No.     | Description                        | List Price | Sale Price |
|---------------|------------------------------------|------------|------------|
| J54-440-740-1 | 4" Digi-Pro Electronic Protractor  | \$82.50    | \$62.80    |
| J54-440-775-1 | 12" Digi-Pro Electronic Protractor | 98.95      | 67.80      |
| J54-100-350   | CR2032 Battery                     | 5.50       |            |

# **PROTRACTORS**

# **BEVEL PROTRACTOR** with 6" & 12" BLADES

- Magnifier for vernier
- · Includes 6" & 12" blades and an angle attachment.
- Satin chrome finish for easy readings in 0-90° sectors.
- · Graduation: 360°
- · Reading to 5 minutes with vernier.
- · Includes fitted case.



| Order No.   | Description      | List Price | Sale Price |
|-------------|------------------|------------|------------|
| J52-440-612 | Bevel Protractor | \$211.70   | \$100.00   |
|             |                  |            |            |

# UNIVERSAL DIAL PROTRACTOR with 6" & 12" BLADES

- · Each dial graduation: 5 minutes
- · Wide spaced graduations
- Hardened stainless steel construction with satin chrome finish for easy reading.
- Includes lock and acute angle attachment.
- · Includes 6" & 12" blades.
- · Supplied in fitted case.



|  | Description List Price Sale Price                | ice |
|--|--|-----|
| J52-440-777 Universal Dial Protractor \$164.65 | Universal Dial Protractor \$164.65 <b>\$98</b> . | 50  |

# **ELECTRONIC UNIVERSAL PROTRACTOR**

with 6" & 12" Blades

- Hardened stainless steel
- Range selection: 1x360°, 2x180°, 4x90°
- Dual reading LCD display arc minutes/decimal degrees
- Preset function
- · 6" and 12" blades and acute angle attachment included.
- · Fine adjustment
- Measuring range: 0-360°
- Resolution: 30 seconds
- Accuracy: ±5 minutes



| Order No.   | Description                     | List Price | Sale Price |
|-------------|---------------------------------|------------|------------|
| J54-440-750 | Electronic Universal Protractor | \$294.50   | \$255.00   |

# **RECTANGULAR HEAD PROTRACTOR**

- · Measures angles from 0-180 degrees
- · Used to transfer angles and to set bevels
- 6" arm with knurled thumb lock nut
- · Made of chrome steel with satin finish
- Measures 3-5/16" x 2". Rectangular head provides four working edges
- Blade secured firmly at any angle by a lock joint and knurled nut



| Order No.   | Description                 | List Price | Sale Price |
|-------------|-----------------------------|------------|------------|
| J52-450-010 | Rectangular Head Protractor | \$49.30    | \$19.95    |

# LEVELS

# **WYLER CLINOTRONIC PLUS**

The Fowler/WYLER Clinotronic Plus is an electronic level with unsurpassed versatility. It is economically priced, uses a specially designed microprocessor and the well-proven WYLER inclination sensor.

- Range of ±45°, capacity of 0-360°
  Resolution of 0.01° (selectable)
- Adjustable base length
- · Built-in calibration program
- Uses standard 1.5v AA batteries
- Desired units to be selected by push
- · Automatic setting of zero by push button command
- · Display: use any units common to inclination measurements
- · Absolute or relative measuring mode selectable by push button
- Seal-tec technology for excellent performance even in difficult environmental conditions
- · Interface connection RS232 is integrated. Specia cables available
- Low battery indication
- · No loss of calibration data by power failure
- · Price includes fitted case

#### Technical Specifications:

- Measuring range/capacity: ± 45°/0-360°
- · Response time: value available within 5 seconds
- Repeatability: <.01°</li>
  Linearity: within 3 min. of arc
- Temp. coefficient: less than 0.01°/°C
- · Data output: Serial
- Battery: Standard AA 1.5V alkaline/130hrs or AA 3.0V Mn02-Lithium (for longer operation 300/hrs)
- · Housing: aluminum hard anodized
- Dimensions: 4 x 3 x 1"(100 x 75 x 30mm)
- Weight: 13 oz.(380 grams)
- Temp. range: operational 0 to 40°C

| EE Fowler Hat th Purchase! | RS-232   | Switt 2mal |
|----------------------------|--|------------|
| ii pui pose                | The following measuring selected: Deg/Arcmin Arcmin / Arcsec | 00° 00     |

| The following measur     | ring ui | nits may be |
|--------------------------|---------|-------------|
| selected:                |         |             |
| Deg/Arcmin               |         | 00° 00'     |
| Arcmin / Arcsec          |         | 00' 00"     |
| GON / Neugrad (2 Dec     | )       | 00.00 gon   |
| GON / Neugrad (4 Dec     | )       | .0000 gon   |
| mm / rel.Basis (2 Dec)   |         | 00.00 mm/m  |
| mm / rel.Basis (4 Dec)   |         | .0000 mm/m  |
| Inch / rel.Basis (4 Dec) |         | .0000"/10"  |
| artillery per mille A‰   |         | 0000        |
| mm / m (2 Dec)           |         | 00.00 mm/m  |
| Inch / 10 Inches         |         | .0000"/10"  |
| Inch / 12 Inches         |         | .0000"/12"  |
| Milliradian              | 00.00   | mrad (2Dec) |
| Milliradian              |         | 0000 mrad   |
| Deg (2 Dec)              |         | 00.00°      |
| Deg (4 Dec)              |         | .0000°      |

+ Clinotronic PLUS

Order No. Description **List Price** Sale Price J54-635-601 Clinotronic Plus \$1875.00 \$1675.00 J54-635-610 Replacement Battery 44 00

# WYLER MAGNETIC PRECISION SPIRIT LEVEL

WYLER Universal Spirit Levels feature an insulated handle. Main vial unit observed from above and from either side. The vial unit is set into a steel tube in a stress free location, and can be adjusted in the body of the Spirit Level by a fine thread and screw system. Hand scraped by Swiss craftsmen. Includes fitted case.

#### Features:

WYLER Magnetic Precision Spirit Level checks and levels cylinders, horizontal and vertical surfaces. Constructed with two prismatic measuring surfaces. Sensitivity .0002" per 10". Magnets to ensure complete adherence to vertical surfaces of parts and vertical arbors or shafts. Operators on milling and boring units, inspectors and fitters work with free hands.





| Order No.   | Description                         | List Price | Sale Price |
|-------------|-------------------------------------|------------|------------|
| J53-422-048 | NEW Magnetic Precision Spirit Level | \$2407.00  | \$2150.00  |

# **SURFACE FINISH**



# PORTABLE ROUGHNESS TESTER II



- · 2 selectable parameters: Ra and Rz
- · Large LCD display
- · Meets ISO and DIN standards
- · N.I.S.T. traceable specimen included
- Uses 9 volt battery (aprox. 3000 measurements)
- · Includes fitted case



- · Stand with swivel
- · A variety of probes

For certain Applications, RS232 is available on certain models (contact the Fowler technical department for more information)



(X-Pro shown with optional stand with swivel.)

#### X-Pro Portable Roughness Tester II

| Order No.   | Description                                    | List Price | Sale Price |
|-------------|--|------------|------------|
| J54-410-500 | Portable Surface Roughness Tester .0004" probe | \$1644.50  | \$1500.00  |
| J54-410-600 | Portable Surface Roughness Tester .0002" probe | 1644.50    | 1500.00    |

### X-Pro Portable Roughness Tester II Stand with Swivel

| Order No.   | Description                  | List Price |
|-------------|------------------------------|------------|
| J54-400-896 | Stand with Swivel Attachment | \$396.00   |

#### X-Pro Portable Roughness Tester II Probes and Accessories

| Order No.   | Description           | Resolutio <mark>n</mark> | List Price |
|-------------|-----------------------|--------------------------|------------|
| J54-400-319 | General Purpose Probe | .0004"                   | \$547.80   |
| J54-400-326 | General Purpose Probe | .0002"                   | 547.80     |
| J54-420-321 | Small Bore Probe      | .0004"                   | 715.00     |
| J54-420-327 | Small Bore Probe      | .0002"                   | 715.00     |
| J54-420-301 | Traverse Chisel Probe | .0004"                   | 715.00     |
| J54-420-302 | Parallel Chisel Probe | .0004"                   | 715.00     |
| J54-420-328 | Groove Bottom Probe   | .0004"                   | 715.00     |
| J54-420-120 | AC Adapter Kit        |                          | 60.50      |

## **ELECTRONIC EDGE FINDERS**





- · Six equally spaced light ports provide visibility at any angle
- · Made in the USA
- · Edge finder lights instantly when stylus touches work edge
- Repeatability: .0002"
- · Works on any conductive metal

J54-575-650

Along with light indication, model #J54-575-650 emits an audible "beep" at time of contact.

| Order No.   | Stylus | Shank | Audible | Battery | List Price | Sale Price |
|-------------|--------|-------|---------|---------|------------|------------|
| J54-575-600 | .200"  | 1/2"  | NO      | 12 volt | \$28.00    | \$22.85    |
| J54-575-625 | .200"  | 1/2"  | NO      | 12 volt | 98.75      | 87.95      |
| J54-575-650 | .400"  | 3/4"  | YES     | 12 volt | 98.75      | 87.95      |

# **EDGE FINDER SET**

- 3/8" x .200" Edge Finder
- 1/2" x .200" Edge Finder
- 1/2" x .200" Combo Edge Finder
- 1/2" x .500" Edge Finder
- · Complete in fitted case.





| Order No.   | Description     | List Price | Sale Price |
|-------------|-----------------|------------|------------|
| J52-575-125 | Edge Finder Set | \$45.70    | \$36.50    |

# **FOWLER/MIRAGE TOOL SET**

patent pending

The Fowler/Mirage Tool Set is an easy and affordable way to set Z depths quickly and accurately!

- · Can be operated directly off table or from machine vise
- Aluminum contact face eliminates carbide chipping on cutting tools
- · Works on any conductive materials
- · Repeatability: .0002"
- Block dimensions: 1" x 2" x 3" (nominal)
- · Batteries included



Slowly lower cutting tool toward Tool Set ...

...indicator will light up upon contact!

| Order No.   | Description            | List Price | Sale Price |
|-------------|------------------------|------------|------------|
| J54-575-750 | Fowler/Mirage Tool Set | \$91.45    | \$69.00    |

### 12" TELESCOPING GAGE

Another great tool for easy and accurate measurements. Under spring tension, the plungers of the gage expand from the center to the size of the hole being measured and are then locked in place using the knurled knob. Final hole size is obtained by measuring over the contacts with a micrometer or vernier caliper.

# 12" Reach!

- · Contact points are constructed of hardened tool steel, precision ground.
- Double action rigid handle with self-centering feature for quick checking of inside measurements
- · Constant spring tension for uniform feel
- Covers a measuring range of 5/16" to 6" with measurable depths of 12"
- Includes fitted vinyl case



|                          |  | · ·                    | 6                     |
|--------------------------|--|------------------------|-----------------------|
| Order No.<br>J52-470-007 | Description NEW 12" Telescoping Gage Set | List Price<br>\$119.00 | Sale Price<br>\$78.50 |



### **2 DIMENSIONAL COAXIAL** INDICATOR SETS

Use the 2D Coaxial Set for accurate component centering and positioning in most machining applications. The 2D Coaxial indicator can be used at any angle and the dial remains stationary during the rotation of the machine spindle.

- · Indicator assembly with 1.6" (42.5mm) diameter dial
- · Graduations and revolution counter .0005" (.01mm)
- · 3 Internal and 3 External feelers
- · Center point feeler
- Restraining arm
- · Complete in a fitted case




GREAT SHOP TOOL!

#### Specifications:

- Length: 6-7/8" (175mm)
- Shank: 3/8" dia. x 7/8" (10mm x 20mm) long
   Feeler ball: 1/8" (3mm) dia.
- Dial readings: 0-50
- · Measuring range: .250" (6mm) axis offset
- Speed—recommended not to exceed approx. 800 RPM
- Locating accuracy to within .0002" (.005mm) of true center
- Capacity depends on feelers installed, but overall range is 5/32-12" (4-300mm) internal diameter; 0-12" (0-300mm) external diameter

| Order No.   | Description           | List Price | Sale Price |
|-------------|-----------------------|------------|------------|
| J52-710-025 | 2D Coaxial Set-Inch   | \$223.10   | \$166.80   |
| J52-710-030 | 2D Coaxial Set-Metric | 223.10     | 166.80     |



J52-710-025

BEST SELLER!

# X-BLOCK SET

#### each @:

- Dimensions: 1-1/2" L x 1-1/4" W x 1-1/4" H.
- Work capacity: Approximately 1"

#### 2 each @:

- Dimensions: 2" L x 1-1/2" W x 1-1/2" H.
- Work capacity: 1-1/2"

#### All feature:

- · Surfaces are square and parallel within .0005"
- V-grooves are square and parallel with all surfaces within .0005"
- · Corresponding dimensions for each pair are alike within .0005"
- · All enclosed in shop-hardened case

| Order No.   | Description        | List Price | Sale Price |
|-------------|--------------------|------------|------------|
| J52-475-500 | X-Blox V-Block Set | \$103.50   | \$85.00    |

# 1-2-3 & 2-4-6 BLOCKS



J52-439-246

- · 23 holes for easy clamping
- · Sold in pairs
- · Useful in layout & grinding work
- Accuracy: ±.0002"/1"
- Matched accuracy: ±.0002"

| Order No.   | Description  | List Price | Sale Price |
|-------------|--------------|------------|------------|
| J52-439-031 | 1-2-3 Blocks | \$84.55    | \$30.00    |
| J52-439-246 | 2-4-6 Blocks | 199.50     | 150.00     |

# STEEL 1-2-3 BLOCKS



- Tolerance: .0001" (squareness per inch)
- Dimensions: 1" x 2" x 3"
- Hardened to 58-60 Rockwell C.
- · Matched accuracy within ±.0002"

| Order No.   | List Price | Sale Price |
|-------------|------------|------------|
| J52-439-001 | \$129.35   | \$55.00    |

# 1/8" PREMIUM PARALLEL SET

- Made from high-grade alloy steel, hardened and ground from 1/8" stock with 2 holes in each parallel
- 10 pairs, 6" length, 1/8" width
- 1/2", 5/8", 3/4", 7/8", 1", 1-1/8", 1-1/4", 1-3/8", 1-1/2" & 1-5/8"
- Height specifications relate to consistency within each pair
- Absolute heights are nominal
- · Parallelism: ±.0002"
- · Paired in height: ±.00015"
- Hardness 58-63 HRC

| Order No.   | Description       | List Price             | Sale Price |
|-------------|-------------------|------------------------|------------|
| J52-437-125 | 1/8" Parallel Set | \$2 <mark>63.20</mark> | \$242.00   |



# 1/4" PREMIUM PARALLEL SET



- Made from high-grade alloy steel, hardened and ground from 1/4" stock with 2 holes in each parallel
- 9 pairs, 6" length, 1/4" width
- 3/4", 7/8", 1", 1-1/8", 1-1/4", 1-3/8", 1-1/2", 1-5/8" & 1-3/4"
- · Height specifications relate to consistency within each pair
- Absolute heights are nominal.
- Parallelism: ±.0002"
- · Paired in height: ±.0002"
- Hardness 52-58 HRC

| Order No.   | Description       | List Price             | Sale Price |
|-------------|-------------------|------------------------|------------|
| J52-437-250 | 1/4" Parallel Set | \$3 <mark>28.90</mark> | \$275.00   |

### THICKNESS GAGES

- Each leaf of the thickness gage made of fine tempered steel, hardened
- · The exact thickness is marked on each leaf
- · Steel case with lock nut
- · Meets U.S. Federal Specifications





| Order No.   | Description                    | List Price   | Sale I       | Price  |         |
|-------------|--------------------------------|--|--------------|--------|---------|
| J52-485-006 | .004", .005", .0               | Thickness Gages-Inch.26 Leaf Set: .0015", .<br>06", .007", .008", .009", .010", .011", .012", .0<br>17", .018", .019", .020", .021", .022", .023", .               | 013", .014", | 614.00 | \$11.99 |
| J52-485-010 | 0.15mm, 0.20n<br>0.50mm, 0.55n | Thickness Gages-Metric. 20 Leaf Set: 0.05mnm, 0.25mm, 0.30mm, 0.35mm, 0.40mm, 0.4<br>nm, 0.60mm, 0.65mm, 0.70mm, 0.75mm, 0.8<br>nm, 0.95mm and 1mm. Length: 100mm. | I5mm,        | 317.60 | \$9.99  |

### **SCREW PITCH GAGES**



#### **Screw Pitch Gages**

- Narrow designed blades permit use for internal and external screw threads
- · Locking device at each end to secure all blades for storage or position
- · Correct pitch is determined by matching blade teeth with threads
- · Precisely ground and finished
- · Blades marked with thread size

#### Acme Screw Pitch Gage (29° angle)

 Made of fine stainless steel. Each blade is 3-1/2"/90mm long and .03"/.8mm thick

| .00 7.011111 1111010                        |   |            |            |
|---|---|------------|------------|
| Order No.                                   | Description   | List Price | Sale Price |
| Inch Series<br>J52-485-015<br>Metric Series | NEW Screw Pitch Gage with 30 blades: 4 to 42 pitch standard V thread  | \$10.45    | \$7.99     |
| J52-485-020<br>Acme Series                  | NEW Screw Pitch Gage with 24 blades: 0.25mm to 6.0mm  | 10.45      | 7.99       |
| J52-485-030                                 | NEW Acme Screw Pitch Gage with 16 blades (1, 1-1/3", 1-1/2", 1-3/4", 2-1/2", 3, 3-1/2", 4, 5, 6, 7, 8, 9, 10 &12 pitch) | 2, 91.30   | 85.00      |

# THREAD MEASURING WIRE SET



- Thread Measuring Wires include 48 wires in sixteen different sizes
- Accuracy for sizes .018" through .108" is within +0 / .0004"; sizes .120" through .185" is within +0 / .0005"
  Measures all U.S. 60° threads from 3-48
- threads per inch
- Laminated conversion chart for 60° U.S and metric threads is included

| Order No.   | Description                             | List Price | Sale Price |
|-------------|---|------------|------------|
| J52-485-048 | NEW Thread Measuring Wire Set: 48 Wires | \$28.00    | \$19.99    |



Acme Screw Pitch Gage J52-485-030

### **RULES**

### EZ-Read Black Face Rules

- · Hardened stainless steel
- White easy-to-read microfine graduations against a black, non-glare finish



J52-297-006

2 3 --- 4 --- 5 - "

J52-330-006

GRADUATIONS
4R: 8ths, 16ths, 32nds, 64ths

5R: 32nds, 64ths, 10ths, 100ths

# Satin Chrome Rules

- Tempered steel
- Non-glare
- Sharp, easy-to-read microfine graduations

Save over 10%

#### Golden Rules

- Titanium coated for superior wear resistance
- Non-glare finish=RC80
- Scratch resistant microfine graduations with excellent clarity and contrast



J52-299-006

BEST SELLER!

#### **RIGID STEEL RULES**

| Order No.   | Finish       | Size | Reading | List Price | Sale Price |
|-------------|--------------|------|---------|------------|------------|
| J52-330-006 | Satin Chrome | 6"   | 4R      | \$9.90     | \$8.60     |
| J52-337-006 | Black        | 6"   | 4R      | 8.35       | 6.25       |
| J52-339-006 | Golden       | 6"   | 4R      | 20.60      | 17.25      |
| J52-330-012 | Satin Chrome | 12"  | 4R      | 17.20      | 14.60      |
| J52-337-012 | Black        | 12"  | 4R      | 17.20      | 10.70      |
| J52-339-012 | Golden       | 12"  | 4R      | 39.55      | 33.80      |
| J52-340-006 | Satin Chrome | 6"   | 5R      | 9.50       | 7.55       |
| J52-347-006 | Black        | 6"   | 5R      | 8.35       | 6.25       |
| J52-349-006 | Golden       | 6"   | 5R      | 20.60      | 17.25      |
| J52-340-012 | Satin Chrome | 12"  | 5R      | 15.60      | 14.60      |
| J52-347-012 | Black        | 12"  | 5R      | 17.20      | 10.95      |
| J52-349-012 | Golden       | 12"  | 5R      | 39.55      | 33.80      |

#### **FLEXIBLE STEEL RULES**

| Order No.   | Finish       | Size | Reading | List Price | Sale Price |
|-------------|--------------|------|---------|------------|------------|
| J52-295-006 | Satin Chrome | 6"   | 4R      | \$9.50     | \$7.05     |
| J52-297-006 | Black        | 6"   | 4R      | 7.80       | 5.75       |
| J52-299-006 | Golden       | 6"   | 4R      | 20.30      | 17.70      |
| J52-295-012 | Satin Chrome | 12"  | 4R      | 14.60      | 13.00      |
| J52-297-012 | Black        | 12"  | 4R      | 12.00      | 9.90       |
| J52-299-012 | Golden       | 12"  | 4R      | 36.40      | 31.20      |
| J52-300-006 | Satin Chrome | 6"   | 5R      | 9.50       | 7.05       |
| J52-307-006 | Black        | 6"   | 5R      | 7.80       | 5.75       |
| J52-309-006 | Golden       | 6"   | 5R      | 20.30      | 17.70      |
| J52-300-012 | Satin Chrome | 12"  | 5R      | 14.60      | 13.00      |
| J52-307-012 | Black        | 12"  | 5R      | 12.00      | 9.90       |
| J52-309-012 | Golden       | 12"  | 5R      | 36.40      | 31.20      |

# 6"/150MM POCKET STEEL RULE

• Rounded edge prevents damage to shirt pocket • Rule width: .470"

- · Inch graduations are in 64ths
- Metric scale is in 1mm increments
- Dula Haialanaan 00

| · Rule thickness: .0 | 21 |
|----------------------|----|
|----------------------|----|

|             |                            |            | Cu High    |
|-------------|----------------------------|------------|------------|
| Order No.   | Description                | List Price | Sale Price |
| J52-380-100 | 6"/150mm Pocket Steel Rule | \$6.25     | \$4.95     |

# **COMBINATION SQUARES**

- · Blades are chrome plated, fully hardened and tempered, graduated in 8ths, 16ths, 32nds and 64ths
- · Finished in black enamel
- · Square head has level and scriber point
- Double indexed protractor is graduated 180° in both directions



| Order No.   | Description                                       | List Price | Sale Price |
|-------------|---|------------|------------|
| J52-373-012 | Square Head with 12" blade                        | \$82.50    | \$73.00    |
| J52-386-006 | Square and Center Head with 6" blade              | 11200      | 50.00      |
| J52-370-012 | Square, Protractor and Center Head with 12" blade | 165.90     | 129.80     |

# **STEEL SQUARES & SETS**

- · Made of the finest carbon tool steel. these economy squares have true right angles both inside and outside
- · Beams and blades ground and lapped for straightness and parallelism
- · Hardened blade

· Carbide scriber Order No.

J54-175-012

J54-175-018

J54-175-024

- · Beam grooved at inner corner for clearance of burrs and dirt
- · Squareness of blade edge to the working face: 2" & 3" = ±.0006", 4" & 6" = ±.0008", 9" & 12" = ±.0012"

| OLIO       |           |  |  |  |
|------------|-----------|--|--|--|
| Blade Size | Beam Size |  |  |  |
| 2"         | 1.5"      |  |  |  |
| 3"         | 2.5"      |  |  |  |
| 4"         | 3"        |  |  |  |
| 6"         | 4"        |  |  |  |
| 9"         | 6"        |  |  |  |
| 12"        | 8"        |  |  |  |

Sets come complete in a "Shop Hardened" molded case!



| Order No.   | Size/Description   | List Price | Sale Price |
|-------------|--|------------|------------|
| J52-432-444 | 3 Piece Square Set: 2", 4" & 6" with shop hardened case      | \$52.00    | \$47.75    |
| J52-432-246 | 4 Piece Square Set: 2", 3", 4" & 6" with shop hardened case  | 61.90      | 53.95      |
| J52-432-469 | 4 Piece Square Set: 4", 6", 9" & 12" with shop hardened case | 103.95     | 102.75     |
| J52-432-004 | 4" Square only   | 18.75      | 17.00      |
| J52-432-006 | 6" Square only   | 20.80      | 18.25      |
| J52-432-009 | 9" Square only   | 41.60      | 38.50      |
| J52-432-012 | 12" Square only  | 70.75      | 64.50      |



Range

0-12"/0-300mm

0-18"/0-450mm

0-24"/0-600mm

J54-100-350 CR2032 Battery

**List Price** 

\$465.90

543.20

611.50

5.50

# 24" TWIN BEAM HEIGHT GAGE

- · Separate digit counters register both upward & downward travel
- · Zero setting can be obtained throughout the gage's range
- Coarse readings in .100" graduations: fine readings taken on indicator are .001"
- Dual chrome plated beams Carbide-tipped scriber
- · Base is hardened, ground & lapped for maximum flatness

| Sale Price         |        |
|--------------------|--------|
| \$331.20<br>391.20 |        |
| 391.20             |        |
| 465.80             | Order  |
|                    | J52-17 |



| Order No.                | Range | List Price | Sale Price |
|--------------------------|-------|------------|------------|
| Order No.<br>J52-174-224 | 24"   | \$682.10   | \$409.50   |

### **METAL ETCHING PEN**

A "must" for any tool room and machine shop for general marking purposes, Fowler's metal etching pen is used on copper, copper alloy, stainless steel, hardened steel tools and castings, etc.




Use it to initial personal tools. Its low-cost, disposable design offers limitless applications.

ETCHING WARKER FOWIER Tint

# Personalize your tools!

| Order No.   | Description   | List Price | Sale Price |
|-------------|---|------------|------------|
| J52-730-005 | NEW Disposable Felt Tip Metal Etching Pen, overall length is 6-1/4" | \$17.35    | \$14.85    |

# **STEEL SCRIBERS**



Chuck holds hardened tempered scriber point, which is removable and replaceable

| Order No.   | Description    | Overall Length | List Price | Sale Price |
|-------------|----------------|----------------|------------|------------|
| J52-515-005 | Pocket Scriber | 5.625"         | \$4.70     | \$2.60     |

- · Fine quality steel blade with fully hardened points
- · Hook point on opposite end

Chrome finished with knurled handle

| Order No.   | Description   | Overall Length | List Price | Sale Price |
|-------------|---------------|----------------|------------|------------|
| J52-515-025 | Point Scriber | 8.5"           | \$4.70     | \$2.60     |

### **CARBIDE TIPPED SCIBER VALUES!**



· Lightweight · Retractable carbide tip · Knurled grip · Machined aluminum body · Pocket clip

| Order No.   | Description           | Overall Length | List Price | Sale Price |
|-------------|-----------------------|----------------|------------|------------|
| J52-500-050 | Carbide Super Scriber | 6.5"           | \$29.90    | \$26.80    |
| J52-500-055 | Carbide Refill        |                | 9.50       |            |



• Lightweight • Retractable carbide tip • Fluted grip • Blue anodized aluminum body • Pocket clip

| Order Number | Description            | Overall Length | List Price | Sale Price |
|--------------|------------------------|----------------|------------|------------|
| J52-500-000  | Pocket Carbide Scriber | 6.0"           | \$16.00    | \$11.50    |
| J52-515-046  | Carbide Refill         |                | 6.05       |            |



Heavy duty
 Replaceable carbide tip
 Knurled grip
 Pocket clip
 Magnetic end cap

| ISO SOO OOO Dania aa bia Tira Oanbida waxaa aa ah aa a |        |        |
|---|--------|--------|
| J52-500-080 Replaceable Tip Carbide w/magnetic end cap 5.75"                      | \$8.60 | \$5.75 |
| J52-500-085 Carbide Refill  | 1.75   |        |

Heavy duty
 Fixed carbide tip
 Pencil-like design
 Pocket clip

Order No.

 Description
 Overall Length
 List Price
 Sale Price

 Order No.
 Description
 Overall Length
 List Price
 Sale Price

 J52-500-090
 Fixed Tip Scriber
 6.0"
 \$5.80
 \$3.50

### SUPER HEAVY DUTY AUTOMATIC CENTER PUNCH




- · Handle constructed in steel. Four knurled bands provide a sturdy grip
- · Moveable components are made from tool steel and hardened
- · The point is easily removed for sharpening
- The pressure of marking is controlled by rotating the knurled cap. Screw the cap down for heavy indentations and screw the cap upward for lighter markings.

| Order No.   | Description                             | List Price | Sale Price |
|-------------|---|------------|------------|
| J52-500-290 | Super Heavy Duty Automatic Center Punch | \$19.80    | \$14.00    |

### **4 PIECE DEBURRING CUTTER SET**

4pc Deburring Cutter Set features four separate color coded cutters. Each color indicates the material that the cutter is intended for.

- Colored sleeves rotate to lock and unlock blades for easy changing
- Unique rounded head for safe deburring of drilled and machined holes, end-milled areas, tubing, backsides of holes, and numerous other uses
- Curved blades swivel freely to automatically follow shapes, contours and holes





NEW!

| Order No.   | Description                | List Price | Sale Price |
|-------------|----------------------------|------------|------------|
| J52-483-777 | 4 pc. Deburring Cutter Set | \$14.85    | \$12.50    |

# X-GLIDE Lubricant and Protectant

- · Specifically formulated for precision tools
- Synthetic lubricant enriched with multiple anti-friction additives
- Sub-micron particle size allows for maximum penetration and durability
- Antistatic additive prevents the attraction of dust and dirt
- dust and dirt

  Contains no solvents, propellants or flam-
- mable gases
   PH neutral
- · 2.5 oz. spray bottle





| Order No.   | Description | List Price | Sale Price |
|-------------|-------------|------------|------------|
| J53-885-105 | NEW X-Glide | \$10.00    | \$7.50     |

# X-TRA RANGE MICROSCOPE

Fowler's Extended Range Microscope is ideal for viewing the surface of items that will not fit conventional microscope plates.



| Order No.     | Description                         | List Price | Sale Price |
|---------------|-------------------------------------|------------|------------|
| J53-640-280   | 20X Microscope with Universal Stand | \$347.15   | \$275.00   |
| J53-640-281-1 | Replacement bulb                    | 11.20      |            |

# **POCKET SCOPE & MICRO-LITE**

Available in 20x or 40x

WIER HIGH PE

### Pocket Scope

- · Fixed focus, no moving parts-never loses focus.
- · Accurate readings without adjusting
- Compact in size, under 5"
- · Provides on-the-job viewing
- Special bevelled opening gathers and focuses light

### Micro-Lite

 Invaluable for inspection and measurement of hard-to-see and reach places



| Order No.   | Description                           | Field of View | Scale Range | List Price | Sale Price |
|-------------|---------------------------------------|---------------|-------------|------------|------------|
| J52-662-020 | 20x Pocket-Scope with .002" reticle   | .190"         | 018"        | \$32.65    | \$25.50    |
| J52-662-040 | 40x Pocket-Scope with .001" reticle   | .082"         | 007"        | 32.65      | 25.50      |
| J52-662-045 | Micro-Light (uses AAA battery not inc | luded)        |             | 23.30      | 12.00      |
| J52-662-050 | 20x Pocket Scope & Micro-Lite Set     |               |             | 54.95      | 35.00      |
| J52-662-055 | 40x Pocket Scope & Micro-Lite Set     |               |             | 54.95      | 35.00      |

### DIGITAL ROCKWELL HARDNESS TESTER

A high quality precision instrument that uses the Rockwell A, B and C scales for measuring hardness. Featuring ease of operation, automatic loading and unloading, automatic holding of test force and an easy-to-read LCD.

#### Features:

- · New, advanced, multi-function indicator readout
- · Full color LED display
- · Built in hardness calculator statistics function
- Standards: EN-ISO 6508 and ASTM-E18
- · Resolution: .02 of a Rockwell unit
- · Test loads: 10 kgf preload/60, 100, 150 kgf load
- · Rockwell scales: A, B, C, F
- Testing space: Vertical = 6.7"/170mm,

Horizontal = 6.5"/165mm (from centerline)

#### Accessories included:

- · Diamond Rockwell indentor
- Rockwell ball indentor 1/16" ±60HRC Hardness test block
- · +25HBC Hardness test block
- · ±85HRB Hardness test block
- Flat anvil 60mm ø
- · Large flat anvil 150mm ø
- · V-anvil 40mm ø
- Adjustable feet
- · Protective spindle cover





| Order No.     | Description                          | List Price | Sale Price |
|---------------|--------------------------------------|------------|------------|
| J54-770-650-1 | NEW Digital Rockwell Hardness Tester | \$5170.00  | \$4653.00  |

# ANALOG ROCKWELL HARDNESS TESTER



A high quality precision instrument that uses the Rockwell A. B. C and F scales for measuring hardness. A reasonably priced solution for those requiring precision and durability.

#### Features:

- Standards: EN-ISO 6508 and ASTM-E18
- Resolution: .5 Rockwell unit
- Test loads: 10 kgf preload/60, 100, 150 kgf load
- Rockwell scales: A. B. C. F
- Testing space: Vertical = 6.7"/170mm,

Horizontal = 6.5"/165mm (from centerline)

#### Accessories included:

- Diamond Rockwell indentor
- Rockwell ball indentor 1/16"
- ±60HRC Hardness test block
- ±25HRC Hardness test block
- ±85HRB Hardness test block
- Flat anvil 60mm ø
- Large flat anvil 150mm ø
- V-anvil 40mm ø
- Adjustable feet
- Protective spindle cover



| Order No.   | Description                     | List Price | Sale Price |
|-------------|---------------------------------|------------|------------|
| J53-770-600 | Analog Rockwell Hardness Tester | \$2194.50  | \$1970.00  |
|             |                                 |            |            |

### **TOOL MASTER LITE TOOL PRESETTER**

Fowler's NEW Tool Presetter Stand for maximum productivity with ultimate user-friendliness. Tool Master Lite is a simple and user friendly presetter.

Introductory Offer 10% off

# NEW!

- · User friendly
- · Swiss quality
- Reduces setup times
- · Measures all types of tooling
- · No connection to power or compressed air needed
- · Needle bearing tool pot can be used with various adaptors, contact Fowler's technical department for details
- · Easy to use digital display for each axis
- · High concentricity needle bearing tool pot
- Maximum measuring repeatability
- · Smooth ball bearing guides

#### **Technical Data**

Measuring Range X axis 9.8"/250mm, Z axis 11.8"/300mm .0008"/.02mm

Accuracy (X and Z)

Fine Adjustment X axis

Tool Mounting

Measuring Method Dimensions

Weiaht 23 ka

Power Battery (AA type)



| Order No.   | Description                         | List Price | Sale Price |
|-------------|-------------------------------------|------------|------------|
| J54-188-777 | NEW Tool Master Lite Tool Presetter | \$6795.00  | \$6115.00  |

# Fowler Mobile Tech Center



# Follow us on Twitter @ Fowler\_MTC





Fowler's Newest & Most Popular
Precision Tools and Technologies are on
the road and going across the country in
Fowler's NEW Mobile Tech Center!

For details and information about getting the Fowler Mobile Tech Center to your location, contact the Vice President of Sales, Jeff Petersen, at jeffp@fvfowler.com





www.fowlerprecision.com

Fowler High Precision

tind us on social media

You FowlerVid

Fowler High Precision

Fowler\_Co